### 1 Author's response

2

The manuscript has been subjected to extensive changes according to the suggestions and comments of the two referees. We hope that in the current version the paper is now suitable for publication on Ocean Science (OS). The changes performed on the text are reported stepby-step below.

7

### 8 <u>Referee #1</u>

9

### 10 <u>Comments from Referee</u>

11 This manuscript presents and describes the Civitavecchia Coastal Environment Monitoring 12 System (C-CEMS). The system integrates several components such as fixed stations, in-situ 13 surveys, satellite observations and numerical models to forecast, evaluate and face pollutants 14 dispersion. Two applications of C-CEMS are presented here: 1) Bacterial dispersion in 15 bathing areas and 2) evaluation of dredged sediments dispersion on Sites of Community 16 Importance (SCI) where Posidonia oceanica exist. In my opinion, the topic and the results 17 obtained in this manuscript are relevant for its contribution to achieve a Good Environmental 18 Status (GES) within the MSFD and for its implications for coastal environments and society. 19 In my opinion, the manuscript is well written, well documented and its methodology and 20 results are supported by previous work of the authors. For these reasons, I believe that this is a 21 study of good quality that I can recommend for its publication. 22 Author's response

The authors appreciate that their work is suitable for the publication in OS according to theReferee#1.

25

### 26 <u>Comments from Referee</u>

Page 1601 lines 7-24. For me is not clear from the text if the "Data processing and standardization" was applied only to the data from fixed stations or to all data produced. If it is only applied to the data from fixed stations I think this should be included in the corresponding subtitled "Fixed stations". If it is not please clarify better here.

31 <u>Author's response</u>

32 "Data processing and standardization" has been reduced and integrated to "Fixed Station",

reported on page 7 in the lines interval 26-32 and on page 8 to the line 19.

1 <u>Comments from Referee</u>

2 Page 1602 lines 3-19: Please add the temporal resolution of your satellite observations. Daily?

3 For me it is not clear from the text if the authors have used algorithms previously developed

4 for the extraction of Chla and TSM using SEADAS or local ones for CASE II waters. Please

5 clarify and add a little more of information about the algorithms used. I suggest the authors to

6 rewrite the paragraph and try to not mix sensors, products and methodologies.

### 7 <u>Author's response</u>

8 The satellite observations are daily downloaded and processed, when available. As also 9 suggested by the referee#2 the paragraph "Satellite Observations" has been rewritten 10 highlighting the data processing chain and the algorithms used to calculate TSM and 11 Chlorophyll a concentrations.

12 This information is reported on page 9 and on page 10 in the lines interval 1-10. The new 13 references related to this argument are included in the:

- page 21 in the lines interval 20-22 (Cristina et al., 2015);
- page 24 in the lines interval 20-22 (Pichel et al., 2001);
- page 25 in the lines interval 7-9 (Santoleri et al., 2008);
- page 25 in the lines interval 1-3 (Qin et al., 2007);
- page 25 in the lines interval 4-6 (Ruddick et al., 2006);
- page 24 in the lines interval 17-19 (Ondrusek et al., 2012);
- page 21 in the lines interval 23-26 (Cui et al., 2014);
- page 22 in the lines interval 16-19 (Drusch et al., 2012).
- 22

### 23 <u>Comments from Referee</u>

Page 10607 lines: 3-7: I would appreciate here a little bit more of information about that consist the in situ samplings, what type of information was registered and how the thematic maps were created. Or in other case, please give a reference where the reader can find this information. How this in situ information was used or is going to be used? Authors show that the suspended sediments can reach zones of *Posidonia oceania*, have they studied some change in these meadows?

30 <u>Author's response</u>

The health status of *Posidonia oceanica* meadows located in the two SCIs has been evaluated by shoot density descriptor. This parameter was acquired by scuba-diver in the late Spring of 2013 following the method reported in Buia et al. 2003. The thematic map is then obtained

- 1 spatially interpolating the data collected in the two areas. The authors has previously studied
- 2 the changes in these meadows due to suspended solid concentration.
- 3 This information is reported in the:
- paragraph 4.2 ("Dredged sediments dispersion on Posidonia oceanica meadows"),
  page 14, lines interval 24-32;
- 6
- paragraph 5 ("Discussion"), page 17, lines interval 11-13;
- 7
- "References", page 20, lines interval 4-6 (Buia et al., 2003).
- 8
- 9 <u>Comments from Referee</u>
- 10 I would suggest the authors add at least one scale and North arrow to have a reference. Fig. 1.
- 11 I would recommend the authors to add a map of Italy here. Thus the reader could locate the
- 12 study area within the Italian region at a first glance. Fig. 7. It is difficult to read the legends of
- 13 these figures, especially B. I suggest making these figures and legends larger.
- 14 <u>Author's response</u>
- 15 The scale bar and the North arrow have been reported in Figure 5 (a and b), 6 (a and b) and 7
- 16 (a and b). The map of Italy has been included in the Figure 1 and the legends of the Figures 7a
- 17 and 7b have been zoomed. The captions of Figure 1 and 7 have also been changed.
- 18
- 19 <u>Comments from Referee</u>
- 20 Page 1603 line 8-9: Eliminate "we solved the"
- 21 <u>Author's response</u>
- 22 "we solved the" has been removed
- 23
- 24
- 25
- 26
- 27
- 28
- 29
- 30
- \_\_\_\_

- 32
- 33

### 1 **<u>Referee #2</u>**

2

3 Comments from Referee

- 4 There are many potential good things about this paper that are still missing and include:
- 5 (1) conveys a good deal of relevant factual information
- 6 (2) update references relevant and useful for the topics especially dealing with the MSFD
- 7 (3) the resource management for coastal issue is timely and important but not well addressed
- 8 (is not even considered the MSP Framework Directive (Directive 2014/89/EU)
- 9 (4) the author(s) could convey familiarity with the Mediterranean region in question not only
- 10 to the local scale,
- 11 (4) EO processing are not in the good-to-excellent range.
- 12 I think there are some serious flaws in the paper structures that makes the presentation really
- 13 difficult to follow. The problem is that the reader comes away from the paper wondering what
- 14 the paper is about. Somehow the assemblage of words, sentences, paragraphs, equations, and
- 15 tables fails to convey a central themes that I know how to paraphrase. This is in part a severe
- 16 problem with organization. All is there.
- 17 The authors need to state that the paper is primarily about a key resource management issue
- 18 related to coastal issue considering MSFD. Then they need to relate the various sections of the
- 19 paper to this
- 20 problem thereby accounting for material in sections, sub-sections, and paragraphs. I cannot
- 21 recommend publication of this paper until I can state what the central themes and sub-themes
- of the paper are.
- 23 Why the author's choose the two applied examples? Are they related? Is the MSFD related to
- both of them and in which way?
- 25 <u>Author's response</u>
- 26 The manuscript has been revised according to this suggestion.
- 27 On page 4 in the lines interval 1-16, the central theme and the sub-themes are better 28 explained.
- The role of MSP and MSFD in the management of coastal uses and in the conservation of marine environment resources has been highlighted in "Introduction" from line 18 to 23.
- 31 A brief description of the physical and biological features of the north eastern Tyrrhenian sea
- 32 (Western Mediterranean region) has been integrated in "Study area" in the lines interval 19-27
- 33 of the page 4. The new references related to this argument are included in the:

1 • page 23 in the lines interval 14-15 (Hopkins, 1988);

3

- page 24 in the lines interval 29-30 (Pinardi and Navarra, 1993);
  - page 26 in the lines interval 4-6 (Vetrano et al. 2010);
- page 24 in the lines interval 27-28 (Pierini and Simioli, 1998).

5 The two applied examples have been chosen to show the C-CEMS capabilities in supporting 6 the management of conflicts between anthropic uses and sensitivity areas ("urban discharge -7 bathing area" and "dredging - SCI" conflicts). Their relation with MSFD is reported on page 8 12 in the lines interval 5-10 and 25-27, on page 14 in the lines interval 11-13. The new 9 reference related to this argument is included in the page 20 in the lines interval 11-12 10 (Caruso, 2014).

In this revised version the key role of the numerical models within C-CEMS has been emphasized since they enable the observational network to analyse and forecast the pollutants dispersion at -appropriate spatial and temporal resolutions. The conflicts are then evaluated overlapping the model results with the thematic maps of the sensitivity areas. This information is reported on page 6 in the lines interval 6-9 and 19-27.

As also suggested by the Referee#1, "Satellite Observation" has been rewritten highlighting the data processing chain and the algorithms used to calculate TSM and Chlorophyll a concentration. The change is reported on page 9 and on page 10 to the line 10. The new references related to this argument are included in the:

- page 21 in the lines interval 20-22 (Cristina et al., 2015);
- page 24 in the lines interval 20-22 (Pichel et al., 2001);
- page 25 in the lines interval 7-9 (Santoleri et al., 2008);
- page 25 in the lines interval 1-3 (Qin et al., 2007);
- page 25 in the lines interval 4-6 (Ruddick et al., 2006);
- page 24 in the lines interval 17-19 (Ondrusek et al., 2012);
- page 21 in the lines interval 23-26 (Cui et al., 2014);
- page 22 in the lines interval 16-19 (Drusch et al., 2012).

The advantages of C-CEMS and the analysis of "urban discharge - bathing area" and "dredging - SCI" conflicts are reported in the new section "Discussion" on pages 16-17.

- 30 The Figure 2 has been modified and better argued (caption at page 32) in order to highlight
- 31 the links between the C-CEMS components and their role in supporting the management of

32 marine environment resources.

According to the authors the large amount of work improves the structure and the
 organization of the paper making it easier its reading and understanding.

3

### 4 <u>Comments from Referee</u>

5 1. The introduction must have way much more background on MSFD and very recent 6 scientific papers on the matter. No need to cover everything, but is good to increase the 7 litterature review especially in respect of MSFD. A cursory literature review turns up 8 numerous examples of similar technical applications on other coastlines with more scientific 9 questions related to MSFD, including:

10 - Cristina, Sónia, et al. "Using remote sensing as a support to the implementation of the 11 European Marine Strategy Framework Directive in SW Portugal." Continental Shelf Research (2015). - Jayasinghe, RP Prabath K., Upali S. Amarasinghe, and Alice Newton. "Evaluation 12 13 of marine subareas of Europe using life history parameters and trophic levels of selected fish populations." Marine Environmental Research (2015). - Pieralice, Francesca, et al. "An 14 15 innovative methodological approach in the frame of Marine Strategy Framework Directive: A 16 statistical model based on ship detection SAR data for monitoring programmes." Marine 17 environmental research 102 (2014): 18-35.

18 <u>Author's response</u>

In "Introduction", new references about the different approaches for the analysis of GES descriptors, including those recommended by the referee, has been reported on page 2 (lines interval 23-32) and 3 (lines interval 1-7). The new references related to this argument are included in the:

- page 21 in the lines interval 20-22 (Cristina et al., 2015);
- page 24 in the lines interval 23-26 (Pieralice et al., 2014);
- page 23 in the lines interval 20-22 (Jayasinghe et al., 2015);
- page 25 in the lines interval 23-25 (Tornero and Ribera d'Alcalà, 2014).
- 27

### 28 <u>Comments from Referee</u>

29 2. The innovation missing from this paper is perhaps the great challenge of remote sensing 30 combined with the insitu analysis and the modelling: once you make the detection of different 31 variables, what do you really increase into the remote sensing community or in the coastal 32 managers community? What specific, physical or ecological insight do C-CEMS approach 33 allow? What exactly do we gain from combined temporal C-CEMS approach that we cannot

determine, for example, from a classical method? The technological advantage and whether or 1

2 not the analysis of that advantage is innovative depends on the research question. At this stage

the paper represent a series of analysis that is unclear how they set up the innovative method. 3

#### 4 Author's response

5 The innovation of this paper concerns the development of the new observation network (C-CEMS) to support the management of marine environment resources solving the coastal 6 7 conflicts between the anthropic uses and sensitivity areas at an appropriate spatial and temporal scale. In this context the "Numerical models" component gives a fundamental 8 9 contribution within C-CEMS, as well as the fixed stations that ensure the availability of a 10 large amount of real-time data allowing the analysis of coastal conflicts by the detection of 11 pollution phenomena. Model results overlapped with the characteristics of the sensitivity 12 areas can be considered as the first step for the establishment of marine functional zoning 13 scheme made by different types of zones with varying levels of limited uses. This information is mainly included in "Conclusions" (pages 17-18) that has been widely modified. The new 14 15 reference related to this argument is included in the page 25 in the lines interval 17-20 16 (Serafino et al., 2012).

17 The in-situ data collected by fixed stations and field survey are then combined with the 18 satellite observations to assign the initial and boundary conditions of the numerical models. 19 The links between C-CEMS components are reported in different parts of the paper:

20

21

in "Fixed stations", page 7, lines intervals 8-24; •

- •
- 22 23

in "In-situ surveys", page 8, lines intervals 23-32;

- in "Satellite observations", page 9 (lines intervals 30-32) and 10 (lines intervals 1-• 3);
- 24

in "Numerical models", page 11, line intervals 10-15. •

25 The new references related to this argument are included in the:

- 26 • page 21 in the lines interval 23-26 (Cui et al., 2014);
- 27 • page 19 in the lines interval 12-14 (Beckers et al., 2006);

29 In the paper we highlighted also how the in-situ and remote observations are used in C-CEMS 30 applications. This information is reported on page 13 in the lines intervals 18-21 and on page 31 15 in the lines intervals 9-11. The new reference related to this argument is included in the 32 page 25 in the lines interval 21-22 (Thoe et al., 2010).

page 26 in the lines interval 7-9 (Volpe et al., 2012). 28 •

### 1 <u>Comments from Referee</u>

2 3. The C-CEMS approach analysis is sound enough, but for a methodological paper, a more robust testing or assessment is needed. There is a light comparison with field based data 3 4 especially within the EO part. There is a new bunch of literature more than the MODIS and AVHRR processing chain considering MERIS and the new Sentinel-2 (Filipponi, F., et al. 5 "GENERATION OF GRIDDED OCEAN COLOR PRODUCTS FROM MERIS: AN 6 7 EFFICIENT PROCESSING CHAIN). Considering the new Copernicus world is the 8 speculation of EO within the paper sound enough? If I also consider what was developed 9 under FP7 EU Project COBIOS and what is under development with the BEAM project 10 (http://www.brockmann-consult.de/cms/web/beam/) I do highlight to the author that the message 11 that additional data processing and analysis can help define boundaries better is no doubt true, 12 but not very enlightening-the same would apply to additional effort paid to others analysis. I 13 do consider the authors expert in the area if they want to relate in management procedure (this 14 part is really confusioning to my knowledge).

### 15 <u>Author's response</u>

16 Since the pollutants dispersion represents the C-CEMS results, the capability of the 17 observation system in reproducing the output of coastal pressures has been evaluated 18 analyzing the accuracy of hydrodynamic field through the use of sea currents (WQB) and 19 wave data (WB2) acquired by fixed stations. This information is reported on the page 11 in 20 the lines intervals 16-18.

The algorithms used to analyse the Chlorophyll a concentration and TSM from MODIS data have been validated with in-situ data measured by water quality station (WQB) and periodic field surveys. In the manuscript the MODIS and AVHRR processing chain has been reported too. This information is included in "Satellite observations", on the page 9 (lines interval 10-32) and 10 (lines interval 1-3). The new references related to this argument are included in the:

- page 24 in the lines interval 20-22 (Pichel et al., 2001);
- page 25 in the lines interval 7-9 (Santoleri et al., 2008);
- page 25 in the lines interval 1-3 (Qin et al., 2007);
- page 25 in the lines interval 4-6 (Ruddick et al., 2006);
- page 24 in the lines interval 17-19 (Ondrusek et al., 2012);
- page 21 in the lines interval 23-26 (Cui et al., 2014).

Accordingly to the Copernicus program, C-CEMS provides a monitoring service for the
 marine environment through multi-source data that include in-situ and remote sensing
 observations. This information is reported on page 6 in the lines intervals 2-6.

4

### 5 <u>Comments from Referee</u>

4. Lastly, but importantly, the manuscript in its current form is crippled by disorganization. 6 7 The Introduction and Results & Discussion sections are sprawling and difficult to follow. I do 8 prefer to see in a scientific paper results and discussion well separated. The Data & physical 9 section is not reasonably clean and is lacking in information, but the Methods & Methodology 10 section is impenetrable with a lack of a simple workflow that could help the reader (Figure 2 11 is not helping the reader in that direction). Wherever it gets published, any subsequent version 12 of this work needs to clarify explicitly the authors' research question, motivation, hypothesis, 13 and outcomes. It is much too long & too detailed (I propose to reduce the length as well as the 14 # of tables and figures with at

least 20%). While reading I had the impression that it was rather a report of a technical projectthan a paper; e.g. the different details used during the paper. You must focus much more on

17 the novelties and skip all superfluous background information & details.

### 18 <u>Author's response</u>

As reported on page 16 in the lines interval 6-8, the purpose of the authors is to write a methodological manuscript that describes the C-CEMS observational network and how it analyses the coastal conflicts.

The paper focused on: (1) the functioning of C-CEMS and its components (Section 3); (2) its capabilities in reproducing the dispersion of fecal bacteria for bathing water quality assessment and of dredged fine sediments to evaluate the effects on *Posidonia oceanica* meadows present in the Sites of Community Importance (SCI) of the Civitavecchia coastal area (Section 4); (3) the resulting analysis of "urban discharge - bathing area" and "dredging -SCI" conflicts (Section 5). This information is reported on the page 4 in the lines interval 1-7. To help the reader to understand the links between C-CEMS components and their role in

supporting the management of marine environment resources, the workflow of Figure 2 hasbeen improved.

In this regard "Data processing and standardization" has been reduced and integrated in "Fixed station" (pages 7-8) and the Table 1 has also been removed (pages 27-28).

1	The authors consider that these changes can improve the structure and organization of the
2	manuscript.
3	
4	
5	The following additional changes, reported below, have also been considered by the
6	authors for the revised version.
7	
8	• In "Abstract", MSP directive has been reported and the description of C-CEMS
9	components and applications has been improved.
10	• The need to study the marine environment resources by monitoring networks,
11	included C-CEMS, in the Mediterranean region has been clarified in
12	"Introduction".
13	• In "Study area" the coastal zone between Marina di Tarquinia and Macchia Tonda
14	has been framed in the Mediterranean region.
15	• In "Components of the C-CEMS" we highlight that the analysis of economic
16	impact, reported also in the Figure 2, has not been evaluated in this work.
17	• In the other part of the manuscript, some technical corrections have been made to
18	improve the structure and organization of the paper.

# The Civitavecchia Coastal Environment Monitoring System (C-CEMS): a new tool to analyse the conflicts between coastal pressures and sensitivity areas

4

5 S. Bonamano<sup>1</sup>, V. Piermattei<sup>1</sup>, A. Madonia<sup>1</sup>, F. Paladini de Mendoza<sup>1</sup>, A. 6 Pierattini<sup>1</sup>, R. Martellucci<sup>1</sup>, C. Stefanì<sup>1</sup>, G. Zappalà<sup>2</sup> and M. Marcelli<sup>1</sup>

[1]{Laboratory of Experimental Oceanology and Marine Ecology (LOSEM), DEB—
University of Tuscia, Molo Vespucci, Port of Civitavecchia, Civitavecchia 00053, Rome,
Italy}

10 [2]{ CNR - Istituto per l'Ambiente Marino Costiero, Messina, Italy}

11 Correspondence to: S. Bonamano (simo\_bonamano@unitus.it)

12

### 13 Abstract

14 The understanding of the coastal environment is fundamental for efficiently and effectively 15 facing the pollution phenomena, as expected by Marine Strategy Framework Directive, and for limiting the conflicts between anthropic activities and sensitivity areas, as stated by 16 17 Maritime Spatial Planningwhich is focused on the achievement of Good Environmental Status (GES) by all Member States by 2020. To address this, the Laboratory of Experimental 18 19 Oceanology and Marine Ecology developed a multi-platform observing network that has been in operation since 2005 in the coastal marine area of Civitavecchia, where multiple uses and 20 21 high ecological values closely coexist. The Civitavecchia Coastal Environment Monitoring System (C-CEMS), implemented in the current configuration, includes various components 22 23 allowing to analyse the coastal conflicts by an ecosystem based approachmodules that provide integrated information to be used in different fields of the environmental research. The long-24 25 term observations acquired by the fixed stations are integrated withby in-situ data collected for the analysis of surveys, periodically carried out for the monitoring of the physical, 26 chemical and biological characteristics parameters of the water column, sea bottom and 27 pollution sources detected along the coast-and marine sediments, as well as of the benthic 28 29 biota. The in-situ data, integrated with satellite observations (e.g. temperature, chlorophyll-a

and TSM), are used to feed and validate the numerical models, which allow the analysis and 1 2 forecasting of the dynamics of conservative and non-conservative particles pollutants 3 dispersion under different conditions. To test the capabilities of C-CEMSAs examples of C-CEMS applications, two case studies are reported in this work: 1) the analysis of fecal 4 5 bacteria dispersion for bathing water quality assessment and; 2) the evaluation of the effects of the dredged activities on Posidonia meadows, which make up most of the two sites of 6 7 community importance located along the Civitavecchia coastal zone. The simulations results 8 are combined with the presence of bathing areas and Posidonia oceanica distribution and 9 bathing areas presence in order to solve the conflicts between coastal uses (in terms of stress produced by anthropic activities) and sensitivity areas-management. 10

### 11 **1 Introduction**

Coastal ecosystems are characterized by the spatial and temporal coexistence of multiple uses connected to many human activities such as aquaculture, energy production, maritime transport, tourism, and fishery. The overlap of such activities and their objectives has the ability to create user-user and user-environment conflicts (Douvere, 2008) that result in increasingly undesirable effects such as loss and destruction of habitat, pollution, climate change, over-fishing, and cumulative threats to the oceans and human health as a whole.

The Integrated Marine Policy (IMP) has faced this issue by the adoption of the Maritime 18 19 Spatial Planning Directive (MSP, 2014/89/EU) whose main purpose is to promote the 20 sustainable management of uses and conflicts in coastal areas through an ecosystem-based approach. MSP strategy allows to minimize the impacts on sensitivity areas, also enabling the 21 achievement of the Good Environmental Status (GES) by 2020, requested by Marine Strategy 22 23 Framework Directive (MSFD 2008/56/EC). In the last years a big effort was made by the scientific community to provide new approaches for the analysis of GES descriptors like the 24 study of eutrophication (descriptor 5) through satellite ocean color data (Cristina et al., 2015) 25 26 and the assessment of sea-floor integrity (descriptor 6) by SAR imagery (Pieralice et al., 27 2014). Important results were also obtained by the analysis of both commercial fishes and foodweb (descriptors 3 and 4), to assess the environmental status of European seas 28 29 (Jayasinghe et al., 2015), and the levels of major contaminants (descriptors 8 and 9) and their 30 pollution effects on aquatic biota (Tornero and Ribera d'Alcalà, 2014). 31 -Within European environmental policy, the Water Frame Directive (WFD, 2000/60/EC) and

32 the Marine Strategy Framework Directive (MSFD, 2008/56/EC) were recently approved to

protect estuarine and coastal seas from increasing pressures and impacts and to move toward 1 2 marine integrative management. Contrary to the WFD, which follows a 'deconstructing 3 structural approach' to achieve a Good Ecological Status for all European water bodies by 2015, the MSFD requires the achievement of a Good Environmental Status GES for all 4 5 European seas by 2020 through a 'holistic functional approach'. A GES is based on the analysis of 11 descriptors that collectively represent the state and functioning of the whole 6 7 system (Borja et al., 2008, 2010). In keeping with the holistic nature of the MSFD, the 8 achievement and the maintenance of European marine ecological standards need the support 9 of monitoring networks which use L-TER observations and integrate multi-disciplinary datasets, fundamental to forecast specific events (Schofield et al., 2002). requires detailed 10 11 knowledge of the pressures exerted on marine environments, monitoring of physical, 12 chemical, and biological components, and analysis of the services provided by ecosystems 13 and the sustainable use of marine resources. However, A-a recent study by Crise et al. (2015) revealed a lackgaps of data in the Mediterranean region (South European Seas) South 14 15 European Seas (SES), highlighting the scarcity, dispersion and heterogeneity of coastal waters datasetsexistence of a clear North-South 'data and knowledge gradient' due to the chronic 16 17 scarcity of marine data. It is accordingly necessary to develop monitoring systems in the 18 southern European coastal areas capable of collecting both high-resolution and long-term data 19 and building multi-disciplinary datasets. The correct management of coastal resources and 20 environments requires climatologies deriving from physical and biological time series data as well as the capacity to forecast specific events (Schofield et al., 2002). Many efforts have 21 been dedicated to the development of coastal ocean observatories, and rRecent advances in 22 23 communication and sensor technology have led to the development of worldwide multi-24 platform networks that provide a significant amount of data on different spatial and temporal 25 scales for the study of oceanographic processes and marine ecosystem monitoring (Glasgow 26 et al., 2004; Hart and Martinez, 2006; Kroger et al., 2009). These monitoring tools are 27 especially suited for coastal systems (i.e., Chesapeake Bay Observing System, CBOS; Li, 28 2005; Long-term Ecosystem Observatory, LEO-15; Schofield et al., 2002) characterized by 29 high spatial and time variability and affected by strong conflicts between human uses and 30 ecosystem conservation. In this context, the Laboratory of Experimental Oceanology and 31 Marine Ecology developed a multi-platform observing network which operates since 2005 in the coastal marine area of Civitavecchia (Italy, Tyrrhenian Sea, Western Mediterranean Sea), 32 33 critically interested by the presence of many conflicts.

This paper presents the C-CEMS as a tool to support the management of conflicts between anthropic uses and sensitivity areas. We focused on: (1) the functioning of C-CEMS and its components (Section 3); (2) its capabilities in reproducing the dispersion of fecal bacteria for bathing water quality assessment and of dredged fine sediments to evaluate the effects on *Posidonia oceanica* meadows present in the Sites of Community Importance (SCI) (Section 4); (3) the resulting analysis of "urban discharge - bathing area" and "dredging - SCI" conflicts (Section 5).

8 In this paper, we provide a thorough description of the Civitavecchia Coastal Environment 9 Monitoring System C-CEMS observational network and its utilization for environmental 10 research. Moreover, we present the main results of C-CEMS applications focusing on the analysis of fecal bacteria dispersion for bathing water quality assessment, and the evaluation 11 12 of the effects of the dredged activities on Posidonia oceanica meadows in the Civitavecchia coastal area in the Italian western Mediterranean Sea. We used the integrated responses 13 provided by C-CEMS to create an observatory and forecast system that can provide rapid and 14 15 comprehensive information for the management of coastal conflicts and the potential effects 16 of pollution.

17

### 18 2 Study area

19 The study area is located along the north-east Tyrrhenian coast (Western Mediterranean sea) 20 (Fig. 1A). The circulation of the Tyrrhenian basin is affected by mesoscale and seasonal variability (Hopkins, 1988; Pinardi and Navarra, 1993; Vetrano et al. 2010). The presence of a 21 22 cyclonic gyre with a very pronounced barotropic component suggests that the wind play likely a major role as a forcing agent (Pierini and Simioli, 1998). Like most of the Italian 23 coast, the north-east Tyrrhenian one counts many tourist and industrial areas primarily used 24 25 for maritime transport and energy production, involving an intense exploitation of marine resources. Nevertheless, it houses several biodiversity hotspots and marine protected areas for 26 27 the conservation of priority habitats and species.

In particular <u>The this</u> study <u>area is focused on coastal zone between extends from</u> Marina di
Tarquinia to <u>and</u> Macchia Tonda in the northern Latium region of Italy, <u>as shown in (Fig.</u>
1<u>BA</u>), <u>and</u>-includinges Civitavecchia city, <u>where all the above mentioned uses could produce</u>
potential conflicts which is a populated area characterized by the coexistence of industrial and
human pressures with environmental resources and values. The Civitavecchia harbor is one of

the largest in Europe in terms of cruise and ferry traffic; it represents a fundamental point of 1 2 commercial exchange in Europe. Thanks to the new Port Regulating Plan, the Port of Civitavecchia has increased its commercial traffic and cruise passenger flow. The 3 Interministerial Committee for Economic Planning (CIPE) approved the final project for the 4 5 'strengthening of Civitavecchia harbor hub – first parcel functional interventions: Cristoforo Colombo embankment extension, ferries and services docks realization'. All of these 6 7 operations involve the handling of significant quantities of sediments; the impacts of dredging 8 on the adjacent natural ecosystems can be varied and difficult to predict (Navar et al., 2007; 9 Windom, 1976; Cheung and Wong, 1993; Lohrer and Wetz, 2003; Zimmerman et al., 2003). 10 In conflict with the port activities, the study area hosts four Sites of Community Importance 11 (SCIs) included in the seventh updated list of the Natura 2000 database based on the Italian 12 Environmental Minister decree as an enactment of the European Commission decision 13 2013/739/EU. SCIs They are characterized by the presence of habitats (*Posidonia oceanica* meadows and reefs of rocky substrates and biogenic concretions) and species (Pinna nobilis 14 15 and Corallium rubrum) enclosed in the attachment 1 and 2 of the European Union (EU) directive 92/43/CEE, which can be affected by direct and indirect impacts of port activities. 16

17 Moreover, the promotion of underwater natural beauty, touristic exploitation connected to the increased cruise traffic and the realization of suitable bathing facilities have led to a drastic 18 19 increase in the population density in Civitavecchia during the summer. Many services are now 20 available for recreation thanks to the several beach licenses granted for food, bathing, 21 mooring of private vessels, and sport activities. An updated list of the Latium Region Office 22 counts 72 beach licences released in 2014 to the municipal districts of Santa Marinella and 23 Civitavecchia. However, this urban development was not associated with an upgrade of the wastewater treatment plant, which often caused the discharge of untreated water into the 24 25 bathing areas to be frequently discharged into bathing areas. This situation is in direct conflict with the recreational use of the coastal zone. Along the coast, between Civitavecchia harbor 26 27 and the Punta del Pecoraro bathing areas, four discharge points have been identified as shown 28 in Fig. 1CB in conflicts with the recreational use of the coastal zone. These discharge points 29 present high concentrations of pathogenic bacteria that have been potentially affected by fecal 30 contamination episodes.

### 1 3 Components of the C-CEMS

2 C-CEMS is a multi-platform observing system implemented in 2005 along the coastal area of Civitavecchia (Latium, Italy) to face the coastal conflicts by an ecosystem-based approach. 3 4 Accordingly to the Copernicus program, C-CEMS provides a monitoring service for the marine environment through multi-source data including in-situ and remote sensing 5 6 observations. In addition, C-CEMS integrates this information within mathematical models 7 that allow to simulate specific events and forecast potential impacts with a high spatial and 8 temporal resolution, necessary to analyse the conflicts in coastal areas (Bonamano et al., 9 2015b). It is analogous to a coupled system in which all of the data are assimilated by 10 mathematical models to forecast specific events or impacts and to improve and optimize survey strategies. The C-CEMS includes different modules (fixed stations, in-situ 11 12 measurements and samplings, satellite observations, and numerical models) that provide integrated information that can be used in different fields of environmental research 13 14 (Bonamano et al., 2015b).

15 As shown in Fig. 2, C-CEMS outcomes can be used to assess the conflicts between the 16 pressures on both marine coastal resources and the environment and human 17 health.components interact between them to assess the coastal pressures analysing the dispersion of pollutant substances coming from the anthropic activities located along the 18 19 Civitavecchia coastal area. Data provided by fixed stations, in-situ surveys, and remote 20 sensing play a crucial role being used as input (I = input in Fig. 2) and for the validation (V =  $(V = 1)^{1/2}$ ) validation in Fig. 2) of the numerical models. They give a fundamental contribution in C-21 CEMS allowing to forecast the dispersion of pollutant substances within the sensitivity areas 22 23 represented mainly by marine protected areas and zones designated for recreational uses 24 (bathing, diving, watersports, fishing, etc.). To analyse the potential conflicts between the pressures on both marine coastal environment and human health, the results of the pollutants 25 dispersion, obtained under different weather conditions, are overlapped with the thematic 26 maps of the sensitivity areas. 27

Since marine coastal ecosystems have been acknowledged as providing the most benefits among all terrestrial and marine ecosystems (Costanza et al., 1997), <u>the appointment</u> <u>ofassigning</u> an economic value to these natural resources is essential for correct planning of marine coastal areas. <u>Nevertheless the economic impact on the natural capital in terms of</u> <u>losses of ecosystem goods and services has not been evaluated in this work.</u> The block diagram (Fig. 2) shows all of the components of the C-CEMS that are outlined in
 the following paragraphs.

3 Fixed stations: The capacity of time series data collection is fundamental to improve the 4 ability to control and forecast spatial and temporal variations in a marine environment. To this end, different fixed stations were installed along the Civitavecchia coast to acquire physical, 5 chemical, and biological data, as shown in Fig.1. In particular, a weather station (WS) 6 7 acquires every 10 min makes it possible to acquire wind speed, wind direction, air 8 temperature, air pressure, humidity and solar radiation.; The wind speed and direction 9 represent the main forcing of the hydrodynamic model while the solar radiation data are used as input in the water quality model. *t*Two buoys (WB1 offshore, WB2 nearshore) measure 10 every 30 min make it possible to collect wave statistical parameters (significant height, peak 11 period, and mean direction).; The wave model is fed with WB1 data and then validated with 12 the wave height data collected by WB2. aAn Acoustic Doppler Profiler, ADP (WCS), 13 deployed in a Barnacle seafloor platform, acquires both current velocity (with an acquisition 14 15 rate of 20 min) - and direction and wave height and direction (at intervals of 3 h).; The current velocity components are employed for the validation of the hydrodynamic model.; tThree 16 water quality fixed stations, one buoy (WQB) outside the Civitavecchia harbor and two 17 coastal stations (WQS1 and WQS2), make it possible to acquire every 20 min sub-superficial 18 19 sea temperature, conductivity (salinity, density), pH, dissolved oxygen, fluorescence of 20 chlorophyll-a, and turbidity. In order to validate the satellite ocean color data, chlorophyll-a (Chla) and total suspended matter (TSM) data acquired by WQB were calibrated with the 21 22 concentrations obtained by the water samples analyses. The physical and biological 23 parameters of the WQS1 and WQS2, as well as those acquired by satellite observations, are used as initial conditions of the water quality model. The details of the C-CEMS sensors and 24 25 platforms are listed in Table 1.

All of the data deriving from the fixed stations are transmitted to a website to enable a first
look at data trends. Furthermore, this arrangement makes it possible to quickly respond in
case of a malfunction. The data are then processed and organized as follows.

WQB and WQS data are processed following the SeaDataNet parameter quality control
 procedures: daily validated datasets are produced in order to monitor in near real time the
 water quality, and Edios xml files are provided for monthly time series and stored following
 ISO 19139 and ISO 19115 formats provided for metadata.

1 Data processing and standardization: Scientific research, particularly interdisciplinary 2 research involving human impacts on the natural environment, depends on access to data 3 provided by observatory networks. As highlighted in the EU INSPIRE directive (2007), the importance of the realization of network infrastructures for data sharing derives from the 4 5 ability to provide useful information. Given the recent growth in large-scale collaborative oceanographic research programs, data quality control is essential. If quality control is not 6 7 ensured, data from different sources cannot be combined or re-used. For this reason, the 8 SeaDataNet (SDN) Infrastructure was developed in the EU FP6 framework program in order 9 to realize an efficient, distributed Pan European marine data management infrastructure for 10 managing large and diverse datasets (Schaap, 2010). Thanks to this initiative, datasets are 11 converted into data and metadata standard format by SDN software and tools. The University 12 of Tuscia (LOSEM) is part of the SDN (under the Istituto Nazionale di Oceanografia e di 13 Geofisica Sperimentale, OGS, collating center). Part of the data collected in the C-CEMS are already processed following the SDN parameter quality control procedures: daily validated 14 15 datasets are produced in order to monitor in near real time the status of water quality, and Edios xml files are provided for monthly time series and stored following ISO 19139 and ISO 16 19115 formats provided for metadata. 17

18 The next step is to apply the processing procedure to all of the data produced by the observing
19 system.

20 In-situ surveys: A spatial extension of the observatory system is provided by in-situ collected 21 data. The sampling strategy is conceived with the scope and context of the project objectives 22 in order to select the most appropriate and efficient sampling approach. The field surveys 23 typically include periodic and ad-hoc activities. The firsts concern the acquisition of the 24 physical, chemical and biological variables of the water column performed by multiparameter 25 probes and sea water samples. Data acquired during periodic surveys are used to validate and 26 integrate the satellite observations in order to give the spatial distributions of the seawater 27 parameters as the initial conditions of the water quality model. The ad-hoc samplings are 28 carried out in order to define the nature and composition of the sea bottom and to analyse the indicators of pollution near the human activities outputs. These data feed the water quality 29 30 model for the estimate of the bottom shear stress, as well as the dispersion and/or the decay of pollutants in the nearshore coastal waters data acquired by multiparameter probes, acoustic 31 32 instruments, water, sediments, and biological samples.

Satellite observations: Remote sensing data are essential to provide synoptic and extensive 1 2 maps of biological and physical properties of the oceans (Schofield et al., 2002). Few studies, 3 among which Cristina et al. (2015), demonstrated the usefulness of remote sensing to support the MSFD, using MEdium Resolution Imaging Spectrometer (MERIS) sensor products. 4 5 SimilarlyIn this work, we exploited both ocean color from the Moderate Resolution Imaging Spectroradiometer (MODIS) sensor and thermal infrared color from the Advanced Very High 6 7 Resolution Radiometer (AVHRR) to obtain daily chlorophyll aChla, total suspended matter 8 (TSM); and sea surface temperature (SST) data. Such sensors data were chosen for their 9 availability both in the region of interest and in the period of C-CEMS data acquisition.

10 Regarding the AVHRR data, they are The MODIS data were downloaded from the NASA website at level L1-A (which contains raw radiance counts, spacecraft and instrument 11 12 telemetry, and calibration data) and processed by the SeaDAS image analysis package that is freely distributed to users by NASA. The AVHRR data were downloaded from the NOAA 13 14 website as a Local Area Coverage (LAC) dataset, at a resolution of 1.1 km. These data arewere then processed using ENVI software, which computes SST images in degrees 15 Celsius, using AVHRR bands 3, 4, and 5 and applying the Multi-Channel Sea Surface 16 Temperature (MCSST) algorithms (Pichel et al., 2001). 17

18 Regarding the MODIS data, we download from the NASA website and process by the 19 SeaDAS image analysis package that is freely distributed to users by NASA. The processing 20 begins with a Level-1A file containing top of the atmosphere (TOA) radiance values recorded by the satellite radiometer. The second step is the Level-2 processing which takes the TOA 21 22 radiance intensities in the Level-1A file and performs atmospheric corrections to derive a 23 Level-2 file of normalized water leaving radiances (nLw), Chla concentration, geophysical 24 parameters and quality control flags. A third step takes the geophysical data contained in the Level-2 file and maps it from the raw satellite perspective to a cylindrical coordinate system. 25 To estimate Chla concentration, MedOC3 bio-optical algorithm is applied (Santoleri et al., 26 2008, Qin et al., 2007), while TSM estimation is derived from the 645 normalized water-27 leaving radiance (645 nLw) by applying the MUMM NIR atmospheric correction (Ruddick et 28 al., 2006; Ondrusek et al., 2012). 29

30 Finally Chla and TSM The results of the chlorophyll a and suspended matter concentration
 31 data collected by WQB and periodic in-situ surveys analyses of in situ water samples were
 32 are used to compare and validate the algorithms used for remote sensing data. We are working

on the implementation of a local algorithm specifically developed in the area of interest 1 2 (CASE II waters) in order to reach a better quantification of Chla and TSM concentrations 3 along the study area (Cui et al., 2014). Our aim was to create a local algorithm for quantifying TSM and chlorophyll a concentrations in CASE II waters in detail to yield a better 4 5 understanding of seasonal variations along these areas. These data are essential for providing synoptic maps of the spatial distribution of sea surface temperature, suspended materials, and 6 7 phytoplankton in coastal waters. Accordingly with the Copernicus vision, the future 8 development of this module considers to integrate EO data coming from the Optical High-9 Resolution Sentinel sensors (Drusch et al., 2012), in order to increase the spatial resolution for a more accurate analysis of coastal dynamic processes. 10

Numerical models: Mathematical models play a key role in the C-CEMS by making it 11 12 possible to analyse coastal processes at high spatial and temporal resolution. In this context, the entire datasets collected by fixed stations, satellite observations, and in-situ samplings 13 were employed as input conditions and as a validation of the numerical simulations. The 14 15 mathematical models used in C-CEMS included the DELFT3D package, specifically DELFT3D-FLOW (Lesser et al., 2004) to calculate marine currents velocity, SWAN (Booij et 16 17 al., 1999) to simulate the wave propagation toward the coast, and DELFT3D-WAQ (Van Gils et al., 1993; Los et al., 2004) to reproduce the dispersion of conservative and non-18 19 conservative substances. The governing equations of these models are described in detail in 20 Lesser et al. (2004) and Bonamano et al. (2015a).

21 The DELFT3D-FLOW model domain is rectangular and covers 70 km of coastal area with 22 the Civitavecchia port located at the center. We applied Neumann boundary conditions on the 23 cross-shore boundaries in combination with a water-level boundary on the seaward side, 24 which is necessary to ensure that the solution of the mathematical boundary value problem is 25 well-posed. Since small errors may occur near the boundaries, we positioned the study area away from the side of the model domain. We solved the The hydrodynamic equations are 26 27 solved on a finite difference curvilinear grid with approximately 39,000 elements. In order to limit computational requirements, we applied a different resolution in the model domain 28 29 extending from  $15 \times 15$  m in the Civitavecchia harbor area to  $300 \times 300$  m near the seaward 30 boundary. We subdivided the water column in the vertical direction into 10 sigma layers with 31 a uniform thickness to ensure sufficient resolution in the near-coastal zone.

Since dynamical processes occurring in coastal areas are modulated by wind and wave conditions (we neglect tidal forcing because it does not exceed 0.40 m over the simulation periods), we obtained the hydrodynamic field by coupling the DELFT3D-FLOW with SWAN that uses the same computational grid. Wind data collected by WS were used to feed DELFT3D-FLOW, and the wave parameters acquired by WB1 (offshore wave buoy) were employed to generate the JONSWAP wave spectra (Hasselmann et al., 1980) as boundary conditions of the SWAN model.

- 8 To resolve the turbulent scale of motion, the values of horizontal background eddy viscosity and diffusivity were both set equal to  $1 \text{ m}^2\text{s}^{-1}$  (Briere et al., 2011), and the k- $\varepsilon$  turbulence 9 closure model was taken into account (Launder and Spalding, 1974). To assign the spatial 10 patterns of physical and biological parameters as initial conditions of DELFT3D-WAQ, the 11 12 satellite observations in the offshore zone and the WQS measures in the nearshore one were used rispectivenly. These data are integrated in the water quality model applying the DINEOF 13 technique (Beckers et al., 2006; Volpe et al., 2012) that reconstructs the missing data along 14 15 the coast and in the areas affected by clouds.
- 16 Since the pollutants dispersion represents the C-CEMS results, the capability of the
- observation system in reproducing the output of coastal pressures has been evaluated
   comparing the model results with sea currents (WQB) and wave (WB2) data.
- The performance of the hydrodynamic models (DELFT3D-FLOW and SWAN) was evaluated
  using the Relative Mean Absolute Error (RMAE) and the associated qualitative ranking
  (excellent, good, reasonable, and poor) (Van Rijn et al., 2003).
- The marine currents resulting from the coupling between DELFT3D-FLOW and SWAN were compared with in-situ measurements collected by WCS from 13–18 January 2015. The velocity magnitude was reproduced with a 'good' accuracy since the RMAE value was less than 0.2. The long-shore and cross-shore components of the marine currents exhibited a higher RMAE: 0.28 and 0.3, respectively. The validation of current speed, cross-shore, and along-shore components is shown in Fig. 3.
- We evaluated the performance of the SWAN model using data acquired by the WB2. We calculated the RMAE both for the entire dataset and for three wave direction intervals: 139– 198°N (1st interval), 198–257°N (2nd interval), and 257–316°N (3rd interval). Considering the entire dataset, the wave height has been accurately simulated (RMAE<0.1), but the model error changes significantly on the basis of the wave direction: the RMAE is higher between

139°N and 198°N (0.26; reasonable agreement) and lower between\_in the 2nd°N and 3rd°N intervals (<0.01; excellent agreement), as reported in Fig. 4.

3

1

2

### 4 4 C-CEMS Applications

5 To test the capabilities of C-CEMS in defining the areas mainly affected by pollutants 6 dispersion, we considered two case studies which concern In this study, C-CEMS has been 7 used to support the assessment of the potential effects produced by untreated wastewater 8 discharge and dredging activities (coastal pressures) on bathing areas and SCIs (sensitivity 9 areas), respectively. To analyse the dispersion of polluted substances in the coastal marine 10 environment, we considered in For both cases two periods scenarios with different weather 11 conditions are considered: one reproduces a low wind intensity and low wave height (low 12 condition, LC), and the other simulates a strong high wind speed and high wave height (high 13 condition, HC).

14

### 15 **4.1 Bacterial dispersion in bathing areas**

The presence of pathogenic bacteria in seawater may cause several illnesses including skin
infections and dangerous gastrointestinal diseases (Cabelli et al., 1982; Cheung et al., 1990;
Calderon et al., 1991; McBride et al., 1998; Haile et al., 1999; Colford et al., 2007).

19 The probability of human infection depends on the exposure time and the concentration of the 20 bacterial load in bathing areas. These parameters are linked to the presence of untreated 21 wastewater discharge in the study area and the local hydrodynamical (currents and waves) and 22 environmental (salinity, temperature, and solar radiation) conditions. Among the bacteria that can damage the health of bathers, Escherichia coli, a Gram-negative enteric bacteria present 23 24 in the feces of humans and warm-blooded animals, is considered to be an indicator of water 25 quality. Although the pathogenic bacteria are neglected by MSFD, microbes are relevant to 26 several GES descriptors, notably Descriptor 1 (D1, Biological Diversity), Descriptor 4 (D4, Foodwebs), Descriptors 5 (D5, Eutrophication), Descriptor 8 (Contaminants) (Caruso, 2014). 27 However, C controlling water quality in bathing waters is required by national (d.lgs 28 29 116/2008) and community environmental directives (2006/7/CE).

Under the umbrella of C-CEMS to provide fecal pollution monitoring, in-situ water samplings
 were performed weekly during the summer 2012 at the discharge points indicated in Fig. 1CB
 to analyse the abundance of *E. coli* according to standard culture methods (APAT CNR, 2003).

5 To define the zones mainly affected by provide a map of the potential effects for bathers, we 6 analyzed the dispersion of pathogenic bacteria in the Civitavecchia bathing area, using we 7 used the Microbiological Potential Risk Area (MPRA), defined as the area over which the E. 8 coli concentration is greater or equal to 1% of the concentration measured at a discharge point 9 (Bonamano et al., 2015a). Since this parameter does not depend on the input load concentration, it can be used for evaluating potential effects on human health. The dispersion 10 of E. coli has been simulated by DELFT3D-WAQ using the mean bacterial concentration 11 12 measured during the summer at the discharge points. The model shows a good performance of 13 reproducing the bacterial load concentration near the discharge points (Zappalà et al., 2015). 14 The LC and HC simulations that last two days were set to occur on August weekends when 15 the beaches are characterized by a larger number of bathers. The distribution of bacterial concentration calculated by DELFT3D-WAQ over the study area depends on the 16 17 hydrodynamic field obtained from coupling between DELFT3D-FLOW and SWAN and on 18 the decay rate proposed by Thoe et al. (2010). It was calculated using the salinity acquired by 19 WQS1, WQS2 and WQB, the surface solar radiation measured by WS, TSM and SST 20 obtained by the integration between satellite observations and WQS stations data-estimated with WQS1, WQS2, and WQB temperature and salinity and the WS solar radiation data. 21

22 The *E. coli* concentration calculated near the discharge points was high when low marine 23 currents (LC) were present, as reported in Fig. 5A. In particular, the area around the PI18 24 point exhibited maximum values of pathogenic bacteria because of the slow dilution of 25 contaminated waters in that area. During intense weather conditions (HC), the E. coli concentration near the discharge points was lower than that calculated in the LC simulation. 26 27 However, the E. coli concentration was distributed over a more extended area, as reported in Fig. 5B. In both simulations, the dispersion of E. coli did not affect the bathing area located to 28 the south of the study area. 29

### **4.2** Dredged sediments dispersion on *Posidonia oceanica* meadows

As previously reported, the port of Civitavecchia has been subjected to extensive dredging between 1 November 2012 and 31 January 2013. During the first phase of the project, the dredging of the channel to access the port of Civitavecchia was conducted by deepening the seabed to a depth of -17 m above mean sea level over an area of approximately 31,000 m<sup>2</sup>. In the ferry dock area, the seabed reaches a depth of -10 m over an area of approximately 123,650 m<sup>2</sup> and -15 m over an area of approximately 51,900 m<sup>2</sup>. The total dredging volume was approximately 918,000 m<sup>3</sup>.

9 Studying sediment resuspension caused by these dredging activities is critical because of its role in the dispersion of particulate matter in the adjacent marine environment in both the 10 sediment and water (Van den Berg et al., 2001). Within MSFD, turbidity due to fine sediment 11 12 dispersion is an indicator reported in Descriptor 1 (D1, Biological biodiversity), Descriptor 5 (D5, Eutrophication) and Descriptor 7 (Hydrographical condition). In this work, we 13 14 considered two out of the four SCIs coded as IT60000005 (434.47 ha) and IT60000006 (745.86 ha) localized in the north and the south of the Civitavecchia harbor, as shown in Fig. 15 1BA. Since Posidonia oceanica makes up most of the SCIs, we focused on studying the 16 effects of dredging activities on the status of the seagrass. Dredging-induced suspended 17 18 sediment transport and deposition may have direct and indirect impacts on this seagrass such 19 as reducing the underwater light penetration and producing the burial of the shoot apical 20 meristems, respectively. The survival of the plant can be compromised if the light availability 21 is less than 3-8% of SI (Erftemeijer and Lewis, 2006) or if low-light conditions persist for 22 more than 24 months (Gordon et al., 1994). The survival rates of *Posidonia oceanica* can also 23 be reduced if the sedimentation rate exceeds 5 cm per year (Manzanera et al., 1995).

24 For these reasons, tThe health status of *Posidonia oceanica* meadows located in the two SCIs 25 has been evaluated by shoot density descriptor. This parameter was acquired by scuba-divers in the late Spring of 2013 in correspondence of 14 stations (3 in IT6000005 and 11 in 26 27 IT6000006) following the method reported in Buia et al. (2003). The thematic map is obtained spatially interpolating the data collected in the two areas. elosest to the harbor (IT 28 29 6000005 and IT 6000006) has been monitored by in-situ samplings. The sampling activity and the results of the analyses allowed us to create a thematic map of the shoot density of the 30 marine phanerogam, which is essential for estimating the direct and indirect impacts of 31 32 sediment dispersion.

The potential impacts due to dredging activities have been evaluated by DELFT3D-WAQ 1 2 simulations assuming a continuous release of fine sediments (< 0.063 mm) in the northern 3 zone of Civitavecchia harbor. The amount of material released during dredging was calculated using a formula from Hayes and Wu (2001) using a resuspension factor of 0.77%, which is 4 5 typical of hydraulic dredges (Anchor Environmental, 2003). The percentage of fine sediment fraction is 8.87% and its density is 2650 kg m<sup>-3</sup> according to sedimentological data collected 6 7 in the area affected by the dredging works. Considering also that the time spent on dredging 8 operations was approximately 3 months (from November 2012 until January 2013), we assumed a continuous release of 0.314 kg s<sup>-1</sup>. TSM distribution, obtained by the integration 9 between satellite observations and WQB data, was used as a proxy of spatial variation of fine 10 11 sediment concentration in the study area to provide the initial conditions of DELFT3D-WAQ. The transport, deposition, and resuspension processes associated with the fine particles was 12 reproduced taking into account a settling velocity of approximately 0.25 m day<sup>-1</sup>, a critical 13 shear for sedimentation of 0.005 N m<sup>-2</sup>, and a critical shear for resuspension of 0.6 N m<sup>-2</sup> 14 (Alonso, 2010). The DELFT3D-WAQ simulations were run over the periods 26 November 15 16 2012 through 3 December 2012 (HC simulation) and 3-10 January 2013 (LC simulation). These time intervals included the dredging period. 17

18 Analogous to the analysis of bacterial dispersion, the fate of dredged sediments within the study area was evaluated over an area in which the suspended solid concentration was greater 19 or equal to 1% of the value estimated at the source point. This area is referred to as the 20 Dredging Potential Impact Area (DPIA). The results of the LC simulation, reported in Fig. 21 22 6A, revealed that the dredged suspended materials were transported into the southern zone of 23 the study area achieving a maximum distance of approximately 2 km from dredging point. In the HC simulation reported in Fig. 6B, the dredged sediment dispersion moved is toward the 24 25 north with higher concentration in the nearshore zone. Although the sediment plume extends 20 km from the source, higher values of suspended solid concentration the DPIA only affects 26 27 the *Posidonia oceanica* meadow closer to the harbor (the southern part of SCI IT 6000005) 28 (Bonamano et al., 2015b). The results of the LC simulation, reported in Fig. 6A, revealed that 29 the dredged suspended materials were transported into the southern zone of the study area relatively close to the source (a maximum distance of approximately 2 km). 30

### 5 Conclusions Discussions

1

2 C-CEMS was implemented in 2005 along the coast of Civitavecchia (Latium, Italy), which is a highly populated area characterized by the coexistence of industrial and human pressures 3 4 with environmental resources and values. It integrates fixed stations, in-situ survey and 5 satellite observations which ensure the availability of a large amount of data allowing the analysis of coastal conflicts by the detection of pollution phenomena. Moreover C-CEMS 6 7 provides an ecosystem-based monitoring tool for the analysis and forecasting of the coastal 8 conflicts thanks to the use of mathematical models. The validation of hydrodynamic models 9 with sea currents (WCS) and wave (WB2) data, shows how C-CEMS is able to reproduce 10 accurately the output of coastal pressures in terms of pollutants dispersion. DELFT3D-FLOW reproduces with good accuracy the velocity components of marine currents, while SWAN 11 calculates the wave height in the nearshore area with an higher skill when the interval 12 direction is 198-316 °N. On the contrary, when the wave direction ranges between 139 °N and 13 198 °N, the capacity of the model is more affected by the increase of diffraction processes due 14 to the Civitavecchia harbor breakwater. 15

- The application of C-CEMS to the two case studies examples allowed to define the MPRAs in
   bathing zones and the DPIAs on SCIs under different weather conditions (HC and LC). The
   overlap of the model results with the thematic maps of the sensitivity areas enabled the
   detection of the coastal areas interested by conflicts.
- We present the application of C-CEMS to two different case examples, which allow us to
  analyze the potential impacts on both the marine environment and human health.
- 22 In the first case, the overlap of MPRAs calculated in LC and HC scenarios shows that most of 23 the bathing areas are affected by high level of bacterial contamination (Fig. 7A). Maximum values areas with high bacterial concentrations of *E. coli* abundance were found near the PI18 24 25 and PP24 discharges because the dilution of the contaminated waters was inhibited by the presence of artificial barriers. These unfavorable conditions may cause possible risks to 26 27 human health and are related to the contamination of potentially infectious microorganisms for bathers. in the nearshore waters. As a result, the bathing facilities located within this zone 28 29 are at risk of suffering significant economic losses. On the contrary, as highlighted by the 30 MPRA shown in Fig. 7A, However the southern bathing area, where more bathers are found, 31 is never affected by E. coli dispersion (Fig. 7A).

1 In the second case study, the simulation results differ among LC and HC scenarios (Fig. 7B) it 2 was possible to observe the potential impacts on *Posidonia oceanica* meadows due to dredging activities, as reported in Fig. 7B. In the LC scenario, DPIA does not overlap the 3 southern SCI (IT 6000006), even though the seagrass meadows are characterized by poorer 4 5 health than in northern SCI. In the-HC-simulation, despite the suspended sediments being transported up to 20 km away from the source point, the area with a higher dredged material 6 7 concentration (DPIA) includes a restricted zone of *Posidonia oceanica* meadow (98.84 ha) in 8 the northern SCI, closer to Civitavecchia harbor, characterized by high shoot density values 9 (between 400 and 550 shoots m<sup>-2</sup>). The fine sediment dispersion reproduced in the LC simulation does not reach the southern SCI (IT 6000006) where the seagrass meadows are 10 11 characterized by poorer health than northern SCIs. A previous study (Bonamano et al. 2015b) 12 shows that after the dredging activities the shoot density values were slightly higher than 13 before, highlighting how this conflicts does not produce a loss of environmental resources.

The results of the two application cases show that C CEMS is suitable for analyzing 'urban discharge bathing area' and 'dredging SCI' conflicts, as well as many other conflicts. C CEMS is therefore a new useful tool for coastal zone management. The results of the C-CEMS observational network are a first step toward environmental and economical sustainable management of conflicts along the Civitavecchia coastal area.

## 19

### 20

6

Conclusions

The main objective of C-CEMS is to provide an observation system for a rapid environmental
 assessment and to forecast the coastal dynamic processes at appropriate temporal and spatial
 resolutions. It can also contribute to the availability of marine observations and coastal data,

24 <u>increasing the knowledge about the environmental status of marine ecosystems. To make C-</u>
 25 <u>CEMS more effective, a flexible X-Band Radar System to continuously measure the sea-state</u>

26 (surface currents and wave field) in the near-shore zone (Serafino et al., 2012) has been
 27 recently integrated. Moreover, to improve the resolution of multi-spectral imagery in the

28 <u>study area, C-CEMS will be soon available to get data also from Sentinel-2 mission.</u>

The final goal of this system study was to use this tool<u>C-CEMS</u> to address potential conflicts among the different human activities that persist on the coast using an ecosystem-based approach as requested by IMP for the EU.. In fact, the demand for resources, services, and

space can exceed the capacity of marine areas to meet all of the demands simultaneously
 (Ehler, 2009).

C-CEMS- allowed to define the output of human activities by the use of 'potentially-polluting 3 4 zoning indicators' as MPRA and DPIA giving the potential impacts produced by pathogenic bacteria and dredged fine sediment on sensitivity areas. Such information overlapped with the 5 6 characteristics of recreational coastal uses and marine ecosystems can be considered as the 7 first step for the establishment of marine functional zoning scheme made by different types of 8 zones with varying levels of limited uses (Douvere-,2008). The last step toward an adequate 9 management and conservation of marine environment resources concerns the quantification of 10 economic impacts related to the losses of ecosystem services and goods through the analysis 11 of the present and future conflicts.can contribute to the achieving GES as requested in the 12 context of the MSFD. C-CEMS can also contribute to the availability of marine observations and coastal data, which increases our knowledge of spatial and temporal variations in 13 environmental status. In this way, public administrators and decision makers can acquire a 14 15 clear view of the ecological and economic potential of a study area to ensure that the spatial planning process, as established by the Marine Spatial Planning Directive (2014/89/EU), can 16 take into account easily accessible information about the importance of ecosystem benefits. 17

18

### 19 Acknowledgements

The authors thank the Environmental Office of Civitavecchia Port Authority for funding the implementation of C-CEMS. The authors also thank their colleagues for continuing support and discussion around the coffee breaks. The authors are also thankful to two anonymous reviewers for providing useful comments that helped in improving a former version of this manuscript. Finally, the authors acknowledge the NOAA CoastWatch Program and NASA's Goddard Space Flight Center, OceanColor Web for data availability.

### 1 References

2 Alonso, J.: Heavy metal pollution and sediment transport in the rhinemeuse estuary, using a

3 2D model Delft3D: Water quality and calamities, Case study Biesbosch. Delft Cluster, Delft,

4 the Netherland, 2010.

5 Anchor Environmental, C.A. L.P : Literature review of effects of resuspended sediments due

6 to dredging operations. Prepared for Los Angeles Contaminated Sediments Task Force, Los

- 7 Angeles, CA, 2003.
- APAT-CNR-IRSA: Manuali e Linee Guida, Metodi Analitici per le Acque 29/2003, III;
  sezione 6000 Metodi microbiologici parte generale; sezione 7000 Metodi per la
  determinazione dei microrganismi indicatori di inquinamento e di patogeni, Rome, Italy,
  2003.
- Beckers, J. M., Barth, A., Alvera-Azcárate, A.: DINEOF reconstruction of clouded images
   including error maps Application to the sea-surface temperature around Corsican Island.
   Ocean Sci., 2, 183–199, 2006.
- Bonamano, S., Madonia, A., Borsellino, C., Stefanì, C., Caruso, G., De Pasquale, F.,
  Piermattei, V., Zappalà, G. and Marcelli, M.: Modeling the dispersion of viable and total
  Escherichia coli cells in the artificial semi-enclosed bathing area of Santa Marinella (Latium,
  Italy), Mar. Pollut. Bull. 95, 141–154, 2015a.
- 19 Bonamano, S., Paladini de Mendoza, F., Piermattei, V., Martellucci, R., Madonia, A., Gnisci,
- 20 V., Mancini, E., Fersini, G., Burgio, C., Marcelli, M. and Zappalà, G.: Mathematical models
- 21 supporting the monitoring of Civitavecchia harbour near Rome, Computational Methods and
- 22 Experimental Measurements XVII, 59, 443-453, 2015b.
- 23 Booij, N., Ris, R.C. and Holthuijsen, L.H.: A third-generation wave model for coastal regions,
- 24 Part I: Model description and validation, J. Geophys. Res., 104, 7649-7666, 1999.
- 25 Borja, A., Bricker, S.B., Dauer, D.M., Demetriades, N.T., Ferreira, J.G., Forbes, A.T. and
- 26 Zhu, C.: Overview of integrative tools and methods in assessing ecological integrity in
- 27 estuarine and coastal systems worldwide, Mar. Pollut. Bull., 56 (9), 1519–1537, 2008.
- 28 Borja, A., Elliott, M., Carstensen, J., Heiskanen, A-S., and Van de Bund, W.: Marine
- 29 management towards an integrated implementation of the European Marine Strategy
- 30 Framework and the Water Framework Directives, Mar. Pollut. Bull., 60, 2175–2186, 2010.

- Briere, C., Giardino A. and van der Werf J.: Morphological modeling of bar dynamics with
   DELFT3d: the quest for optimal free parameter settings using an automatic calibration
   technique, Coastal Engineering Proceedings: sediment<sub>1</sub>-<u>1(32)</u>60, 2011.
- 4 Buia M.C., Gambi M.C., Dappiano M. I sistemi a fanerogame marine. In: Gambi M.C.,
- 5 Dappiano M. (Editors). Manuale di Metodologie di campionamento e studio del benthos
- 6 marino mediterraneo. Biol. Mar. Med, 19 (Suppl.):145-198, 2003.
- Cabelli, V.J., Dufour, A.P., McCabe, L.J. and Levin, M.A.: Swimming-associated
  gastroenteritis and water quality, Am. J. Epidemiol., 115, 606–616, 1982.
- 9 Calderon, R. L., Mood, E. W. and Dufour, A. P.: Health effects of swimmers and nonpoint 10 sources of contaminated water, Int. J. Environ. Health Res., 1, 21–31, 1991.
- <u>Caruso, G. Marine Strategy Framework Directive: Current Gaps in Microbiological Issues, J</u>
   <u>Ecosys Ecograph, 4:2 doi:10.4172/2157-7625.1000e120, 2014</u>
- Cheung, W., Chang, K., Hung, R. and Kleevens, J. : Health effects of beach water pollution in
  Hong Kong, Epidemiol. Infect., 105(1), 139–162, 1990.
- Cheung, Y.H. and Wong, M.H.: Toxic effects of dredged sediments of Hong Kong coastal
  waters on clams. Environ. Technol., 14, 1047–1055, 1993.
- 17 Colford, J. M., Wade, T. J., Schiff, K. C., Wright, C. C., Griffith, J. F., Sandhu, S. K., Burns,
- 18 S., Sobsey, M., Lovelace, G. and Weisberg, S. B.: Water quality indicators and the risk of
- 19 illness at beaches with nonpoint sources of fecal contamination, Epidemiology, 18(1), 27–35,
- 20 2007.
- Commission Implementing Decision 2013/739/EU of the European Commission adopting a
   seventh updated list of sites of Community importance for the Mediterranean biogeographical
   region (notified under document C 7356), 2013.
- 24 Costanza, R., d'Arge, R., de Groot, R.S., Farber, S., Grasso, M., Hannon, B., Limburg, K.,
- Naeem, S., O'Neill, R., Paruelo, J., Raskin, R., Sutton, P. and van den Belt, M.: The value of
  the world's ecosystem services and natural capital, Nature 387, 253–260, 1997.
- 27 Council Directive 92/43/EEC of 21 May 1992 on the conservation of natural habitats and of
- wild fauna and flora, Official Journal, L 206/7, 1992.
- 29 Crise, A., Kaberi, H., Ruiz, J., Zatsepin, A., Arashkevich, E., Giani, M., Karageorgis, A.P.,
- 30 Prieto, L., Pantazi, M., Gonzalez-Fernandez, D., Ribera d'Alcalà, M., Tornero, V,

2 Angel, D., Altukhov, D., Avata, S.D., Aktan, Y., Balcioğlu, E., Benedetti, F., Bouchoucha, M., Buia, M.C., Cadiou, J.-F., Canals, M., Chakroun, M., Christou, E., Christidis, M.G., 3 4 Civitarese, G., Coatu, V., Corsini-Foka, M., Cozzi, S., Deidun, A., Dell'Aquila, A., 5 Dogrammatzi, A., Dumitrache, C., Edelist, D., Ettahiri, O., Fonda-Umani, S., Gana, S., Galgani, F., Gasparini, S., Giannakourou, A., Gomoiu, M.-T., Gubanova, A., Gücü, A.-C., 6 7 Gürses, Ö., Hanke, G., Hatzianestis, I., Herut, B., Hone y, R., Huertas E., Irisson, J.-O., Isinibilir, M., Jimenez, J.A., Kalogirou, S., Kapiris, K., Karamfilov, V., Kavadas, S., Keskin, 8 9 C., Kideys, A.E., Kocak, M., Kondylatos, G., Kontogiannis, C., Kosyan , R., Koubbi, P., 10 Kušpilic', G., La Ferla, R., Langone, L., Laroche, S., Lazar, L., Lefkaditou, E., Lemeshko, 11 I.E., Machias, A., Malej, A., Mazzocchi, M.-G., Medinets, V., Mihalopoulos, N., Miserocchi, 12 S., Moncheva, S., Mukhanov, V., Oaie, G., Oros, A., Öztürk, A.A., Öztürk, B., Panayotova, 13 M., Prospathopoulos, A., Radu G., Raykov V., Reglero, P., Reygondeau, G., Rougeron, N., Salihoglu, B., Sanchez-Vidal, A., Sannino, G., Santinelli, C., Secrieru, D., Shapiro, G., 14 Simboura, N., Shiganova, T., Sprovieri, M., Stefanova, K., Streftaris, N., Tirelli, V., Tom, M., 15 16 Topalog'lu, B., Topçu, N.E., Tsagarakis, K., Tsangaris, C., Tserpes, G., Tug'rul, S., Uysal, Z., 17 Vasile, D., Violaki, K., Xu J., Yüksek, A. And Papathanassiou E.: A MSFD complementary 18 approach for the assessment of pressures, knowledge and data gaps in Southern European 19 Seas: The PERSEUS experience, Mar. Pollut. Bull., 95(1), 28–39, 2015.

Vassilopoulou, V., Durrieu de Madron, X., Guieu, C., Puig, P., Zenetos, A., Andral, B.,

- 20 Cristina, S., Icely, J., Goela, P. C., DelValls, T. A., Newton, A.: Using remote sensing as a
- 21 support to the implementation of the European Marine Strategy Framework Directive in SW
- 22 Portugal. Cont. Shelf Res., doi:10.1016/j.csr.2015.03.011, 2015
- 23 Cui, T., Zhang, J., Tang, J., Sathyendranath, S., Groom, S., Ma, Y., Zhao, W, Song, Q.:
- 24 Assessment of satellite ocean color products of MERIS, MODIS and SeaWiFS along the East
- 25 China Coast (in the Yellow Sea and East China Sea), ISPRS Journal of Photogrammetry and
- 26 <u>Remote Sensing</u>, 87, 137-151, 2014.

- 27 Directive 2000/60/EC of the European Parliament and of the Council of 23 October 2000
- 28 establishing a framework for Community actions in the field of water policy. Official Journal
- 29 of the European Communities L327, 1. 22.12.2000. 20
- 30 Directive 2006/7/EC of the European Parliament and of the Council of 15 February 2006
- 31 concerning the management of bathing water quality and repealing Directive 76/160/EEC,
- 32 Official Journal of the European Union, L 64/37, 2006.

- 1 Directive 2007/2/EC of the European Parliament and of the Council of 14 March 2007
- 2 establishing an Infrastructure for Spatial Information in the European Community (INSPIRE),
- 3 Official Journal of the European Union, L 108/1, 2007.
- 4 Directive 2008/56/EC of the European Parliament and of the Council of 17 June 2008,
- 5 establishing a framework for community action in the field of marine environmental policy
- 6 (Marine Strategy Framework Directive), Official Journal of the European Union L164,
- 7 Official Journal of the European Union, L 164/19, 19–40, 2008.
- 8 Directive 2014/89/EU of the European Parliament and of the Council of 23 July 2014
  9 establishing a framework for maritime spatial planning, Official Journal of the European
  10 Union, L 257/135, 2014.
- Decreto Legislativo 30 maggio 2008, n. 116, Attuazione della direttiva 2006/7/CE relativa
  alla gestione della qualità delle acque di balneazione e abrogazione della direttiva
  76/160/CEE, Gazzetta Ufficiale della Repubblica italiana, n. 155, 2008.
- Douvere, F.: The importance of marine spatial planning in advancing ecosystem-based sea
  use management, Mar Policy, 32, 762–771, 2008.
- 16 Drusch, M., Del Bello, U., Carlier, S., Colin, O., Fernandez, V., Gascon, F., Hoersch, B.,
- 17 Isola, C., Laberinti, P., Martimort, P., Meygret, A., Spoto, F., Sy, O., Marchese, F. Sentinel-2:
- 18 ESA's optical high-resolution mission for GMES operational services. Remote Sens. Environ.,
- 19 <u>120, 25-36, 2012.</u>
- 20 Ehler, C. and Douvere, F.: Marine spatial planning: a step-by-step approach toward
- 21 ecosystem-based management. Paris, UNESCO: Intergovernmental Oceanographic
- 22 Commission and Man and the Biosphere Programme, IOPTF. Interim Report of the
- 23 Interagency Ocean Policy Task Force. Executive Office of the President, 1–38, 2009.
- Erftemeijer, P.L.A. and Lewis, R.R.R.: Environmental impacts of dredging on seagrasses: A
  review, Mar. Pollut. Bull., 52, 1553–1572, 2006.
- 26 Glasgow, H. B., Burkholder, J. M., Reed, R. E., Lewitus, A. J., and Kleinman, J. E.: Real-
- time remote monitoring of water quality: a review of current applications, and advancements
- in sensor, telemetry, and computing technologies. J. Exp. Mar. Bio. Ecol., 300(1), 409-448,
- 29 2004.

- 1 Gordon, D.M., Grey, K.A., Chase, S.C. and Simpson, C.J.: Changes to the structure and
- 2 productivity of a Posidonia sinuosa meadow during and after imposed shading, Aquat. Bot.,
- 3 47, 265–275, 1994.
- 4 Haile, R.W., White, J.S., Gold, M.R., Cressey, C., McGee, R.C., Millikan, A., Glasser, N.,
- 5 Harawa, C., Ervin, P., Harmon, J., Harper, J., Dermand, J., Alamillo, K., Barrett, M., Nides,
- 6 G. and Wang, Y.: The health effects of swimming in ocean water contaminated by storm
- 7 drain runoff, Epidemiol., 10, 355–363, 1999.
- 8 Hart, J. K. and Martinez, K.: Environmental Sensor Networks: A revolution in the earth
  9 system science? Earth-Sci. Rev., 78(3), 177-191, 2006.
- 10 Hasselmann, D. E., Dunckel, M. and Ewing, J. A.: Directional wave spectra observed during
- 11 JONSWAP 1973. Journal of physical oceanography. 10(8), 1264-1280,1980.
- 12 Hayes, D. and Wu, P. Y.: Simple approach to TSS source strength estimates, in: Proceedings
- 13 of the WEDA XXI Conference, Houston, TX, USA, 25–27 June 2001.
- Hopkins, T. S.: Recent observation on the intermediate and deep water circulation in the
   southern Tyrrhenian Sea, Oceanol. Acta, 9, special issue, pp. 41-50, 1988.
- 16 ISO/TS 19139: 2007 Geographic information Metadata XML schema implementation,
- 17 International Organization for Standardization, Geneva, Switzerland, 2007.
- 18 ISO 19115-1:2014 Geographic information Metadata Part 1: Fundamentals, International
- 19 Organization for Standardization, Geneva, Switzerland, 2014.
- 20 Jayasinghe, R. P. K., Amarasinghe, U. S., Newton, A.: Evaluation of marine subareas of
- 21 Europe using life history parameters and trophic levels of selected fish populations, Mar.
- 22 Environ. Res., doi:10.1016/j.marenvres.2015.08.002, 2015
- 23 Kröger, S., Parker, E. R., Metcalfe, J. D., Greenwood, N., Forster, R. M., Sivyer, D. B., and
- Pearce, D. J.: Sensors for observing ecosystem status, Ocean Sci., 5(4), 523-535, 2009.
- 25 Launder B.E. and Spalding D.B.: The numerical computation of turbulent flows. Comput.
- 26 Meth., Appl. Mech. Engin., 3, 269–289, 1974.
- Lesser, G.R., Roelvink, J.A., van Kester, J.A.T.M. and Stelling, G.S.: Development and
  validation of a three dimensional morphological model, Coastal Eng., 51, 883-915, 2004.

- 1 Li, M., Zhong, L., and Boicourt, B.: Simulation of Chesapeake Bay Estuary: sensitivity to
- 2 turbulence mixing parameterizations and comparison with hydrographic observations, J.
- 3 Geophys. Res., 110, C12004, doi:10.1029/2004JC002585, 2005.
- Lohrer, A.M., and Wetz, J.J.: Dredging–induced nutrient release from sediments to the water
  column in a southeastern saltmarsh tidal creek. Mar. Pollut. Bull., 46, 1156–1163, 1993.
- 6 Los, F. J., Tatman, S., and Minns, A. W.: Flyland a future airport in the North Sea? An
- 7 integrated modelling approach for marine ecology, 6th International Conference on
- 8 Hydroinformatics, edited by: Liong, S. Y., Phoon, K. K., and Babovic, V., World Scientific,
- 9 Publishing Co.Pte. Ltd. Singapore, ISBN 981-238-787-0, 21–24 June 2004.
- Manzanera, M., Pérez, M. and Romero, J.: Seagrass mortality due to oversedimentation: an
  experimental approach, Journal of Coastal Conservation, 4. 67-70, 1995.
- 12 McBride, G., Salmond, C., Bandaranayake, D., Turner, S., Lewis, G. and Till, D.: Health
- 13 effects of marine bathing in New Zealand, Int. J. Environ. Health Res., 8, 173–18, 1998.
- 14 Nayar, S., Miller, D. J., Hunt, A., Goh, B. P. L., and Chou, L. M.: Environmental effects of
- dredging on sediment nutrients, carbon and granulometry in a tropical estuary. Environ.
  Monit. Assess., 127(1-3), 1-13, 2007.
- 17 Ondrusek, M., Stengel, E., Kinkade, C. S., Vogel, R. L., Keegstra, P., Hunter, C., Kim, C.:
- 18 The development of a new optical total suspended matter algorithm for the Chesapeake Bay,
- 19 <u>Remote Sens. of Environ., 119, 243-254, 2012.</u>
- 20 Pichel, W., Maturi, E., Clemente-Colón, P., Sapper, J.: Deriving the operational nonlinear
- 21 <u>multichannel sea surface temperature algorithm coefficients for NOAA-15 AVHRR/3. Int. J.</u>
   22 <u>of Remote Sens., 22(4), 699-704, 2001.</u>
- 23 Pieralice, F., Proietti, R., La Valle, P., Giorgi, G., Mazzolena, M., Taramelli, A., Nicoletti, L.
- 24 An innovative methodological approach in the frame of Marine Strategy Framework
- 25 Directive: A statistical model based on ship detection SAR data for monitoring programmes.
- 26 Mar. Environ. Res., 102, 18-35, 2014.
- 27 Pierini S. and Semioli A.: Wind-driven circulation model of the Tyrrhenian Sea area. J.
- 28 <u>Marine Syst. Vol 18, pp 161–178, 1998.</u>
- 29 Pinardi, N. and Navarra, A.: Baroclinic wind adjustment processes in the Mediterranean Sea.
- 30 Deep-Sea Res. Pt 2, Vol. 40, No. 6, pp. 1299-1326, 1993.

- 1 Oin, Y., Brando, V. E., Dekker, A. G., Blondeau-Patissier, D.: Validity of SeaDAS water constituents retrieval algorithms in Australian tropical coastal waters, Geophys. Res. Lett., 2 3 34(21), 2007. Ruddick, K. G., De Cauwer, V., Park, Y. J., Moore, G.: Seaborne measurements of near 4 5 infrared water-leaving reflectance: The similarity spectrum for turbid waters. Limnol. and Oceanogr., 51(2), 1167-1179, 2006. 6 7 Santoleri, R., Volpe, G., Marullo, S., Nardelli, B. B.: Open waters optical remote sensing of 8 the Mediterranean Sea, In Remote sensing of the European seas (pp. 103-116), Springer 9 Netherlands, 2008. 10 Schaap, D. and Maudire, G.: SeaDataNet Pan-European infrastructure for marine and ocean 11 data management: unified access to distributed data sets. Technical Aspects International 12 Conference on Marine Data and Information Systems, Paris, France, 29-31 March, available at: www.seadatanet.org, 2010. 13 Schofield, O., Bergmann, T., Bissett, P., Grassle, J. F., Haidvogel, D. B., Kohut, J., Moline, 14 M., and Glenn, S. M.: The long-term ecosystem observatory: an integrated coastal 15 16 observatory, IEEE J. Oceanic Eng., 27, 146–154, 2002. 17 Serafino, F., Lugni, C., Ludeno, G., Arturi, D., Uttieri, M., Buonocore, Zambianchi, E., 18 Budillon, G., and Soldovieri.: F. REMOCEAN: A flexible X-band radar system for sea-state 19 monitoring and surface current estimation. Geoscience and Remote Sensing Letters, IEEE, 20 9(5), 822-826, 2012. 21 Thoe, W.: A daily forecasting system of marine beach water quality in Hong Kong. Ph.D. 22 Thesis, The University of Hong Kong, 2010 23 Tornero, V., and d'Alcalà, M. R.: Contamination by hazardous substances in the Gulf of 24 Naples and nearby coastal areas: A review of sources, environmental levels and potential 25 impacts in the MSFD perspective, Sci. of the Total Environ., 466, 820-840, 2014. 26 Van den Berg, G. A., Meijers, G. G., van der Heijdt, L. M., and Zwolsman, J. J.: Dredging-27 related mobilisation of trace metals: a case study in the Netherlands, Water Res., 35(8), 1979-28 1986, 2001. 29 Van Gils, J.A.G., Ouboter, M.R.L. and De Rooij, M.N.: Modelling of water and sediment
- 30 quality in the Scheldt Estuary, Netherland J. Aquat. Ecol., 27(2-4), 257-265, 1993.

- Van Rijn, L. C., Walstra, D. J. R., Grasmeijer, B., Sutherland, J., Pan, S., and Sierra, J. P.:
   The predictability of cross-shore bed evolution of sandy beaches at the time scale of storms
   and seasons using process-based profile models, Coast. Eng., 47(3), 295-327, 2003.
- 4 Vetrano A., Napolitano E., Iacono R., Schroeder K., Gasparini G.P.: Tyrrhenian Sea
- 5 Circulation and water mass fluxes in spring 2004: observations and model results. J. Geophys.
- 6 <u>Res., Vol. 115 Issue C6, 2010.</u>
- 7 Volpe, G., Nardelli, B. B., Cipollini, P., Santoleri, R., Robinson, I. S.: Seasonal to interannual
- 8 phytoplankton response to physical processes in the Mediterranean Sea from satellite
- 9 observations, Remote Sens. Environ., 117, 223-235, 2012.
- Windom, H.L.: Environmental aspects of dredging in the coastal zone. Crit. Rev. Env. Contr.,
  6, 91–109, 1976.
- 12 Zappalà, G., Caruso, G., Bonamano, S., Madonia, A., Piermattei, V., Martellucci, R., Di
- 13 Cicco, A., Pannocchi, A., Stefanì, C., Borsellino, C. and Marcelli, M. A multi-platform
- 14 approach to marine environment assessment in Civitavecchia (Rome) area. Journal of
- 15 Operational Oceanography, 2015. (In review)
- Zimmerman, L. E., Jutte, P. C. and Van Dolah, R. F.: An environmental assessment of the
  Charleston Ocean Dredged Material Disposal Site and surrounding areas after partial
  completion of the Charleston Harbor Deepening Project, Mar. Pollut. Bull., 46(11), 14081419, 2003.
- 20
- 21
1

## \_Table 1. Specifications of C-CEMS sensors and platforms.

## (WS) WEATHER STATION SPECIFICATIONS

	Range	Accuracy	Resolution
Wind Speed	$060 \text{ m s}^{-1}$	± 2%	<del>0.01 m s<sup>-1</sup></del>
Wind Direction	<del>0360°</del>	±3	<u>1°</u>
Air Temperature	-40+60°C	<u>± 0.3 K</u>	
Relative Humidity	<del>0100 %</del>	<del>1.50%</del>	<del>0.50%</del>
Air Pressure	<del>6001060 mbar</del>	± 0.5 mbar	<u>± 0.05 mbar</u>
Total solar radiation	4 <del>001100 nm</del>	<del>± 3%</del>	± 0.05
Precipitation		<del>0.1 mm</del>	$\pm 1\%$ till 10 mm h <sup>-1</sup>

## (WCS) WAVE-CURRENT STATION SPECIFICATIONS

	Range	Accuracy	Resolution
Current Velocity	$\pm 10 \text{ m s}^{-1}$	±1% meas. Vel.	<del>0.1 cm s<sup>-1</sup></del>
Compass/tilt sensor		±1° (Heading)	<del>0.1°</del>
		±1° (Pitch,Roll)	
Wave Height (strain gage pressure sensor)		<del>0.10%</del>	
Wave Direction	<del>0360°</del>		<u>+1°</u>

#### (WB1-2) WAVE BUOYS SPECIFICATIONS

	Range	Accuracy	Resolution
<del>Wave Height</del>	<del>±20 m</del>	better then 1%	<del>0.01 m</del>
Period	<del>1.533 sec</del>	better then 1%	<del>0.1 sec</del>
(WQB) BUOY SPECIFICATIONS			
	Range	Accuracy	<b>Resolution</b>

Pressure	<del>0.100dbar</del>	<del>0.10%</del>	<del>0.03%</del>
<del>Temperature</del>	<del>-3+50°C</del>	<del>0.003°C</del>	<del>0.0005°C</del>
Conductivity	<del>06.4 S m</del> <sup>-4</sup>	<del>0.0003-S<sup>-1</sup></del>	<del>0.0001_S</del> - <sup>4</sup>
<del>pH</del>	<del>014</del>	<del>0.01</del>	<del>0.001</del>
Dissolved oxygen	<del>050 ppm</del>	<del>0.1 ppm</del>	<del>0.1 ppm</del>
Chlorophyll a Fluorescence	<del>05 μg L<sup>-1</sup></del>	<del>0.025 μg L<sup>-1</sup></del>	
<del>Turbidity</del>	<del>0100 NTU</del>	<del>0.05 NTU</del>	

## (WQS1-2) COASTAL STATIONS SPECIFICATIONS

	Range	Accuracy	Resolution
Pressure	<del>0.100dbar</del>	<del>0.10%</del>	<del>0.03%</del>
Temperature	<del>-3+50°C</del>	<del>0.003°C</del>	<del>0.0005°C</del>
Conductivity	<del>06.4 S m<sup>-1</sup></del>	<del>0.0003 S<sup>-1</sup></del>	<del>0.0001_S<sup>-1</sup></del>
<del>pH</del>	<del>014</del>	<del>0.01</del>	<del>0.001</del>
Dissolved oxygen	<del>050 ppm</del>	<del>0.1 ppm</del>	<del>0.1 ppm</del>
Chlorophyll a Fluorescence	<del>05 μg L<sup>-1</sup></del>	<del>0.025 μg L<sup>-1</sup></del>	
Turbidity	<del>0100 NTU</del>	<del>0.05 NTU</del>	

1

ī





Figure 1. Location of the study area along the north-east Tyrrhenian coast of Italy (Western Mediterranean sea)Study area with the location of coastal uses, SCIs, and measurement stations indicated (A). and zZoom-in on the area of C-CEMS applications: the location of coastal uses, SCIs, and measurement stations indicated (B) and the Civitavecchia bathing areas with discharge points and bather density indicated (1 umbrella corresponds to 5 bathers)
(BC). The fixed station pictures are reported in the bottom-left corner of the figure.





Figure 2. The functioning of C-CEMS for the analysis of the conflicts between coastal pressures and sensitivity areas. The C-CEMS components interact between them to transfer data (by input (I) and validation (V)) from the in-situ and satellite observations to numerical models in order to reach a temporal and spatial resolution enough to analyse the pollutants dispersion in coastal waters. The conflicts are evaluated overlapping the model results with the thematic maps of the sensitivity areas. The economic impact of the conflicts on the marine environment and human health is reported, even though it is not analysed in this work Block diagram of C-CEMS.



Figure 3. Validation of current speed (A), cross-shore (B), and along-shore (C) components.
The solid and dotted lines represent the measured and computed time series, respectively.
Statistics (RMAE) for current speed, cross-shore, and along-shore components are reported in
panel D.



Figure 4. Validation of the SWAN model using RMAE values calculated both for the entiredataset and for three wave direction intervals.



5 Figure 5. LC (A) and HC (B) simulations results of the bacterial dispersion in the 6 Civitavecchia bathing areas. The distribution of *E. coli* concentration refers to the end of the 7 simulation period.

- 8
- 9





Figure 6. LC (A) and HC (B) simulations results of the dispersion of dredged materials in the study area. The distribution of fine sediment concentration refers to the end of the simulation period.





Figure 7. Overlap between anthropic pressures indicated by the 'potentially-polluting zoning indicators' (MPRA and DPIA) simulation results and sensitivity areas represented as thematic maps to analysze 'urban discharge bathing area' (A) and 'dredging SCI' (B) conflicts.