Ocean Sci. Discuss., 7, 361–389, 2010 www.ocean-sci-discuss.net/7/361/2010/ © Author(s) 2010. This work is distributed under the Creative Commons Attribution 3.0 License.



This discussion paper is/has been under review for the journal Ocean Science (OS). Please refer to the corresponding final paper in OS if available.

# Seismic imaging of a thermohaline staircase in the western tropical North Atlantic

### I. Fer<sup>1</sup>, P. Nandi<sup>2</sup>, W. S. Holbrook<sup>3</sup>, R. W. Schmitt<sup>4</sup>, and P. Páramo<sup>5</sup>

 <sup>1</sup>Geophysical Institute, University of Bergen, Allégaten 70, 5007, Bergen, Norway
 <sup>2</sup>BP America, Inc., EPT Advanced Seismic Imaging Deployment, 501 Westlake Park Blvd, Houston, TX 77079, USA
 <sup>3</sup>Dept. of Geology and Geophysics, University of Wyoming, Laramie, WY 82071, USA
 <sup>4</sup>Dept. of Physical Oceanography, Woods Hole Oceanographic Institution, Woods Hole, MA 02543, USA

<sup>5</sup>BP Exploration, Bldg H, Chertsey Road, Sunbury-on-Thames, TW16 7LN, UK

Received: 8 February 2010 – Accepted: 21 February 2010 – Published: 24 February 2010

Correspondence to: I. Fer (ilker.fer@gfi.uib.no)

Published by Copernicus Publications on behalf of the European Geosciences Union.





#### Abstract

Multichannel seismic data acquired in the Lesser Antilles in the western tropical North Atlantic indicate that the seismic reflection method has imaged an oceanic thermohaline staircase. Synthetic modeling of observed density and sound speed profiles corroborates inferences from the seismic imagery. Laterally coherent, uniform layers are present at depths ranging from 550–700 m and have a separation of ~ 20 m, with thicknesses increasing with depth. Reflection coefficient, a measure of the acoustic impedance contrasts, associated with the interfaces is one order of magnitude greater than the background levels. Hydrography sampled in previous surveys puts a constraint on the longevity of these layers in this area to within a maximum of three years.

- straint on the longevity of these layers in this area to within a maximum of three years. Spectral analysis of layer horizons in the thermohaline staircase indicates that internal wave activity is anomalously low, suggesting weak internal wave-induced turbulence and mixing. Results from two independent measurements, the application of a finescale parameterization to observed high-resolution velocity profiles and direct mea-
- <sup>15</sup> surements of turbulent dissipation rate, confirm the low levels of turbulence and mixing. The lack of internal wave-induced mixing allows for the maintenance of the staircase. Our observations show the potential that seismic oceanography can contribute to an improved understanding of temporal occurrence rates, and the geographical distribution of thermohaline staircases and can improve current estimates of vertical mixing <sup>20</sup> rates ascribable to salt fingering in the global ocean.

#### 1 Introduction

Thermohaline staircases are regular, well-defined step-like variations in vertical profiles of temperature and salinity that can occur when vertical temperature and salinity gradients share the same sign (Kelley, 1984). In the ocean, they are the result of double difference defined by the difference definition of the same sign (Kelley, 1984).

fusion driven by the difference in molecular diffusivities for heat and salt (Turner, 1973).
 In a statically stable setting, density-compensating profiles of temperature and salinity



can lead to double-diffusive convection for a top-heavy temperature profile (e.g., typical above the subsurface warm Atlantic Water in the Arctic Ocean, Kelley et al., 2003), and to salt fingers for a top-heavy salinity profile (Stern, 1960; Schmitt, 2003). Double diffusion is shown to influence the efficiency of diapycnal mixing (across constant den-

- sity surfaces), for both diffusive convection (Sundfjord et al., 2007) and salt fingering (St. Laurent and Schmitt, 1999) regimes. Here, we discuss the situation where both salinity and temperature decrease with depth, i.e. when a warmer salty body of water overlies a colder fresher body typical for example in the subtropical ocean, leaving conditions favorable for the development of salt finger staircases. Finger instabilities cause
  small-scale convection cells that can induce significant vertical fluxes at high-gradient
- interfaces between well-mixed layers with contrasting temperature and salinity.

Studies have long suggested that salt fingering can greatly affect the vertical transport of heat and salt in the thermocline and play a significant role in maintaining the global thermohaline stratification (Schmitt et al., 1987, 2005). Salt fingering may play a

- role in the tightness and shape of the mean temperature-salinity relation in the central waters of subtropical gyres (Schmitt, 1981, 1990). Numerical modeling by Zhang and Schmitt (2000) shows that the stability of thermohaline circulation is highly dependent on a critical freshwater flux value, which is reduced in the presence of salt fingering. Results of the North Atlantic Tracer Release Experiment, conducted near the Canary
- Islands, indicated an enhancement of saline diffusivity over thermal diffusivity of more than 60% by salt fingering. The mixing rates inferred from tracer dissipation measurements were better explained with the presence of salt fingering (St. Laurent and Schmitt, 1999). More recently, the Salt Finger Tracer Release Experiment (SFTRE) revealed that vertical mixing was greatly enhanced by the presence of a salt fingering thermal diffusivity of a salt fingering.
- thermohaline staircase with a factor of two enhancement of the haline mixing rate over the thermal mixing rate (Schmitt et al., 2005).

The importance of salt finger processes to ocean structure and circulation emphasizes the need to understand their temporal and spatial occurrence in the environment. The application of models, tracer experiments, and laboratory studies to the





open ocean is still poorly understood. Further insights can be gained from improving observational capabilities: our study utilizes geophysical techniques to observe physical processes over a large spatial area in the ocean, which has the potential to add significantly to the body of staircase observations available to the oceanographic com-<sup>5</sup> munity.

New research in marine geophysics has demonstrated the ability of the multichannel seismic reflection method, sensitive to abrupt vertical changes in sound speed and density, to provide images of physical oceanic processes with exceptional horizontal resolution. Holbrook et al. (2003) first related water-column reflections to oceanic finestructure in a front between the Labrador Current and the North Atlantic Current. Descriptive introductions on the seismic reflection method with focus on water column interpretations can be found in Fer and Holbrook (2008), Ruddick et al. (2009),

10

and Pinheiro et al. (2010). Temperature-salinity contrasts in the water column result in small changes in sound speed and appear in seismic images as distinct reflector
 <sup>15</sup> layers revealing exceptional detail at order 10 m horizontal resolution throughout the full water column. Spectacular images of thermohaline finestructure in the ocean include features such as intrusions (Holbrook et al., 2003), fronts (Holbrook et al., 2003; Nakamura et al., 2006), water mass boundaries (Nandi et al., 2004), internal waves (Holbrook and Fer, 2005; Krahmann et al., 2008), internal tide characteristics (Hol-

- <sup>20</sup> brook et al., 2009) and mesoscale eddies (Biescas et al., 2008; Pinheiro et al., 2010). A clear relationship has been established between recorded seismic reflectance and the presence of thermohaline finestructure (Nandi et al., 2004). A detailed derivation in Ruddick et al. (2009) shows that seismic imaging is essentially a smoothed vertical derivative of temperature on the scale of the acoustic wavelet (order of 10 m). On av-
- erage, 80% of reflectivity (Sect. 2.2) is due to temperature contrasts (Sallarès et al., 2009), whereas the typical contribution of salinity anomalies to reflectivity is about 20% (Sallarès et al., 2009; Ruddick et al., 2009). The latter does not affect the patterns on the final seismic image, since the vertical gradients of salinity and temperature are tightly correlated.

#### OSD

7, 361–389, 2010

# Seismic imaging of a thermohaline staircase

I. Fer et al.





Here, we present a seismic transect from an area previously shown to be prone to salt-finger staircase development, in the western tropical North Atlantic near the Lesser Antilles (Schmitt et al., 1987). Seismic data are supplemented by oceanographic measurements of hydrography, currents and microstructure, and synthetic modelling. Data

- and methodology are presented in Sect. 2. In Sect. 3.2, we demonstrate the enhanced reflectivity associated with the thermohaline staircase. By modeling a synthetic seismic response to physical parameters, we show that seismic reflections can provide a highresolution image of a thermohaline staircase (Sect. 3.3). Assuming that the reflectors oscillate with isopycnals, we infer the internal wave field from spectral analysis of seis-
- <sup>10</sup> mic data, to show weak internal wave activity in the staircase and provide support from oceanographic measurements (Sect. 3.5). Subsequently, we put a constraint on the longevity of the staircase observed in an earlier hydrography survey (Sect. 3.4). Results from independent sampling and analysis are self-consistent and provide evidence that seismic oceanography is capable of detecting the structure and distribution of ther-<sup>15</sup> mohaline staircases. The seismic reflection method may be used to analyze processes
- 15 monaline staircases. The seismic reflection method may be used to analyze processes that affect thermohaline finestructure and provide new observational insights into physical oceanography.

#### 2 Experimental methods

#### 2.1 Data

- The seismic data were acquired on board the R/V Maurice Ewing from 15 March through 6 April 1998 (Bangs, 1998). An air-gun array composed of 20 air-guns with a combined volume of 8420 cubic inches (~ 138 I) generated acoustic energy with shot intervals of 50 m. Reflected energy was recorded on a 4.1-km-long streamer containing 164 hydrophone groups, resulting in a horizontal subsurface sampling spacing of the table.
- 12.5 m. Data were digitized at 250 samples per second, stacked, corrected for spherical divergence and filtered through a minimum-phase trapezoidal band pass filter before 2D Kirchhoff migration.



In this study, we present results from Line D2, which was acquired from west to east across the Caribbean Sea (Fig. 1). Close to the seismic line, full-depth profiles of conductivity temperature depth (CTD), and currents were collected using the High Resolution Profiler (HRP, Schmitt et al., 1988), during the Salt Finger Tracer Release

- Experiment Part 2 (SFTRE-2) cruise on board the R/V Seward Johnson between 29 October and 4 December 2001 (Fig. 1, stars). The physical oceanography sampling is thus more than three years after the seismic transect. HRP is a free-fall profiler sampling finestructure (CTD and horizontal current) at 10 Hz and microstructure (temperature, conductivity and shear) at 200 Hz, at a nominal descent rate of 0.6 m s<sup>-1</sup>.
- Data processing follows mature routines and can be found, for example, in Polzin and Montgomery (1998). Here, 0.5 m vertical resolution profiles of finescale CTD and velocity, and dissipation rate of turbulent kinetic energy are used. The location of Line D2 and the HRP stations is within the limits of the aircraft-deployed expendable bathythermograph survey of the 1985 Caribbean-Sheets And Layers Transects (C-SALT) experiment (Schmitt et al., 1987), and approximately 220 km north of the C-SALT CTD tow-yo section. In order to calculate the reflection coefficients in a well-defined strong
- thermohaline staircase, we make use of a C-SALT CTD tow-yo profile (not shown, see Fig. 3 of Schmitt et al., 1987).

The seismic reflection data from the area at depths of the staircase indicate a dominant return frequency of about 30 Hz (or a wavelength of approximately 50 m), with a spectral content of 5 to 100 Hz. A CTD profile from HRP indicates an average sound speed of 1491 m s<sup>-1</sup> between 550 and 850 m (the depth range of the thermohaline staircase identified in Sect. 3.1). At 100 Hz, an acoustic wave propagating through the water column at this speed should have a maximum limit of vertical resolution of

<sup>25</sup> a quarter of its wavelength (Widess, 1973), in this case about 4 m. Thus, the seismic reflection method should be able to distinguish layers as thin as 4 m.



#### 2.2 Reflectivity

Acoustic impedance, *I*, is the product of density  $\rho$ , and sound speed, *c*; both typically vary with depth in the ocean:  $I(z) = \rho(z)c(z)$ . Reflection coefficient or reflectivity,  $R_i$ , is a measure of the impedance contrast at boundaries. See Ruddick et al. (2009) and

- <sup>5</sup> Sallarès et al. (2009) for a detailed discussion on the relative contribution of temperature and salinity on reflectivity in seawater. In Sect. 3.2 we contrast reflectivity derived from hydrographic observations and seismic data. For the latter, reflection coefficients were derived from a time-migrated seismic profile using a constant sound speed of 1500 m s<sup>-1</sup>. The amplitude of the sea floor ( $A_{sf}$ ) and its first multiple ( $A_{mult}$ ) were used
- to normalize the amplitudes of the reflections in the staircase  $(A_0)$  using  $R_i = A_i/A_0$ , where  $A_0 = -(A_{sf}^2)/A_{mult}$  (Warner, 1990). Diffractions at the sea floor underneath the staircase reported incorrect amplitudes and travel times for the reflectors, necessitating the inclusion of time-migration as an additional processing step. After migration, the sea floor was moved up into a more consistent position in comparison to its location on
- adjacent common depth profiles, and sea floor amplitudes had less interference from other reflectors. The choice of constant sound speed, however, leads to a reduction in signal-to-noise ratio and can mask features revealed by using in-situ sound speed profiles (Fortin and Holbrook, 2009).

From observations, reflection coefficients were calculated using CTD tow-yo data collected during the C-SALT survey in 1985. For continuous profiles of  $\rho(z)$  and c(z), the water column can be approximated as a sequence of layers allowing the calculation of the reflectivity coefficient between two adjacent layers *i* and *i* + 1 as  $R_i = (I_i - I_{i+1})/(I_i + I_{i+1})$ . Consistent with the seismic profiling vertical resolution, a vertical quantization interval of 4 m was applied, after high-pass filtering at 50 m vertical scale (the wavelength corresponding to the dominant acoustic frequency of the seismic profiling).

## OSD 7, 361–389, 2010 Seismic imaging of a thermohaline staircase I. Fer et al. **Title Page** Introduction Abstract Conclusions References Tables Figures Back Close Full Screen / Esc **Printer-friendly Version** Interactive Discussion

#### 2.3 Synthetic modelling

Using a CTD profile from HRP, synthetic modelling of seismic traces is conducted to characterize the pattern of reflectivity expected from finestructure in a thermohaline staircase. Density and sound speed profiles between 10 and 1474 m depth were averaged over 4 m intervals to create a 364 layer representation of the water column. The

aged over 4 m intervals to create a 364 layer representation of the water column. The final model used 164 receivers and a streamer length of 4.1 km to match the seismic data sampling (Sect. 2.1).

#### 2.4 Spectral analysis

Vertical displacements of reflections from oceanic finestructure recorded in the Nor-<sup>10</sup> wegian Sea were shown to be representative of the internal wave field (Holbrook and Fer, 2005). In order to infer the internal wave energy level from spectral analysis, we digitized representative reflector horizons at 12.5 m horizontal resolution, and categorized them into groups based on their proximity to the staircase. Reflector depths were linearly detrended to produce vertical displacements from the mean reflector position.

- <sup>15</sup> Horizontal wavenumber spectra were then calculated with a Welch Fourier transform using 128 point long (1600 m) Hanning windows. The resulting spectra were scaled by the mean buoyancy frequency, *N*, within the depth span of the selected reflector. The buoyancy frequency is approximated from the potential density anomaly  $\sigma_{\theta}$  (referenced to zero surface pressure) as  $N = \left[-g/\rho \partial \sigma_{\theta}/\partial z\right]^{1/2}$  where *z* is depth, *g* is gravitational acceleration and  $\rho$  is the reference seawater density. A survey-averaged *N* profile is
- calculated over 30 m vertical scale using the CTD profiles from HRP dives shown in Fig. 1.

## OSD 7, 361–389, 2010 Seismic imaging of a thermohaline staircase I. Fer et al. **Title Page** Introduction Abstract Conclusions References Tables Figures Back Close Full Screen / Esc **Printer-friendly Version** Interactive Discussion

#### 3 Results and discussion

#### 3.1 Thermohaline staircase

In the spring of 1998, the seismic Line D2 in the Lesser Antilles (Fig. 1) captured patterns suggestive of a salt finger thermohaline staircase (Fig. 2). At least 4 km in length,

- the staircase is composed of four thick, regular, nearly horizontal reflectors with a vertical spacing of about 20 m, consistent with the structure expected from high-gradient interfaces separating mixed layers. Layer thicknesses, measured as peak to peak distance between superjacent wavelets, increase with depth from about 19 m to 25 m. This structure located about 185 km east of Guadeloupe visible at depths between 550 and
- <sup>10</sup> 700 m, is distinguished by its clarity, strong amplitude, lack of modulations and slope. The banded quality of this structure is not an artifact of sampling or signal processing and here, it is suggested to be representative of the thermohaline staircase. The bands represent a stack of regular and uniformly spaced layers, not present anywhere else in the section.
- <sup>15</sup> Decades of data collected in the western tropical North Atlantic show that the conditions favorable for the formation of thermohaline staircases are present permanently in this area (Schmitt, 2003). The representative hydrography inferred from HRP dive 125 is shown in Fig. 3. The water column is composed of Subtropical Underwater, a high salinity water mass that overlies Antarctic Intermediate Water, characterized by a
- <sup>20</sup> salinity minimum. Together, these bodies present a decreasing profile of salinity and temperature with depth, necessary for staircase development. Taken within the C-SALT site, seismic Line D2 crosses an area with strong staircases during the spring of 1985, and lies at the border between strong and weak staircases in the Fall of 1985 (Fig. 1). The existence of a thermohaline staircase is thus quite likely in this region.
- <sup>25</sup> Because turbulent mixing may disrupt the regular structure of thermohaline staircases, they are most apparent where interactions from internal waves, rough topography, boundary forcing and other processes affecting flow stability do not significantly affect their characteristic step-like signature. The staircase imaged in the seismic line

## OSD 7, 361–389, 2010 Seismic imaging of a thermohaline staircase I. Fer et al. **Title Page** Introduction Abstract Conclusions References Tables Figures Back Close Full Screen / Esc **Printer-friendly Version** Interactive Discussion

extends about 11 km westward from its position in Fig. 2 at ~ 212 km to about 189 km, but reflective horizons become less regular and have lower amplitudes at ~ 175 km with the deepest high gradient layer disappearing altogether in places. The strength of the vertical salinity gradient,  $S_z$ , relative to the temperature gradient,  $T_z$ , can be expressed in terms of the density ratio,  $R_\rho = \alpha T_z / \beta S_z$ , where  $\alpha$  and  $\beta$  are the thermal expansion and haline contraction coefficients. We calculate  $R_\rho$  from 0.5-m resolution CTD profiles after estimating the gradients as the slope of linear fits to temperature and salinity against depth in 30 m moving segments. Diffusion is strong for density ratios between 1 and 2 and increases as  $R_\rho$  approaches unity (Schmitt, 1981). Strong staircases with well-defined layers and interfaces are found where density ratio is less than 1.7, and structure becomes irregular for  $R_\rho$  near 2. Profiles of temperature and  $R_\rho$  are

- shown in Fig. 4 for the HRP dives. Density ratios are low, approaching unity, for short segments of the profiles, most continuously in dive 123, where relatively well-defined steps are observed. Although the density ratio favors staircase development for all profiles, strong velocity and shear (Fig. 5) disrupt the vertical structure. The weak velocity and shear recorded in dive 123 allows for the presence of a staircase where  $R_{\rho}$  <
- 1.5. Detailed profiles of temperature and salinity, sound speed and  $R_{\rho}$  inferred from this dive are shown in Fig. 6, in the depth range between 400 and 650 m. Observed temperature and salinity finestructure indicates three well-defined high-gradient steps
- separating four layers at depths between 520 and 630 m (Fig. 6). Layer thickness increases with depth from about 16 to 35 m. Changes in density are small (not shown) because salinity and temperature largely compensate for each other, but abrupt variations in sound speed are large and occur over depth scales similar to those recorded in the temperature finestructure.

#### 25 3.2 Reflection coefficients

How does the reflectivity change through a thermohaline staircase? Although the HRP dive 123 shows a staircase, it is somewhat irregular and weak. We therefore use a profile from C-SALT tow-yo survey to exemplify the reflectivity signature in a staircase.



Repeat temperature profiles (during C-SALT) revealed the staircase where  $R_{\rho} \sim 1.6$ , between 300 and 600 m with 5- to 30-m-thick mixed layers separated by 1- to 10-mthick high-gradient interfaces (not shown, see Fig. 3 of Schmitt et al., 1987). A reflection coefficient profile, calculated here using a CTD profile from C-SALT, shows large spikes corresponding to sharp changes in sound speed from layers in the step-like structure (Fig. 7). We next calculate the reflection coefficients from the seismic Line D2, along a 4-km section centered at the structure resembling a staircase (inset in Fig. 1). In the section of the seismic survey centered on the staircase, reflection coefficients show high values with respect to background noise that are laterally coherent throughout the

<sup>10</sup> profile (Fig. 8). Absolute values calculated from the seismic data are slightly larger than those from the C-SALT CTD, which may be attributed to errors from noisy data and constructive interference of neighboring high amplitude wavelets. We conclude, however, the reflectivity pattern inferred from the seismic data set is consistent with that expected from a staircase and is indicative of the strength of temperature and salinity contrasts between mixed layers.

#### 3.3 Synthetic analysis

We can estimate the seismic reflection signature expected from the HRP dive 123 staircase by conducting synthetic seismic modeling (Sect. 2.3). Synthetic seismic traces created from density and sound speed profile from dive 123 (Fig. 9) show several hyperbolic reflections corresponding to changes in sound speed seen in Fig. 6. Shortly after a high-amplitude linear direct arrival, reflections become visible at a depth of about 200 m. Staircase reflectors are the first strong packet of reflectors to arrive after the direct arrival between 500 and 640 m (assuming a sound speed velocity of 1500 m s<sup>-1</sup>), which match the depths with high gradients in the sound velocity profile.

The unique step-like banded appearance is seen in both the synthetic and the seismic data (compare insets in Figs. 2 and 9). Reflections with high amplitudes relative to their surroundings are laterally coherent, continuous and closely spaced, and resemble the observed staircase structure in Line D2, which lies ~ 110 km to the west of the station



location (Fig. 1). Because the synthetic seismic transect shows all the layers at the correct depths, we conclude that the seismic reflection method is capable of imaging the variations in finestructure that characterize a thermohaline staircase.

#### 3.4 Longevity

Though strong staircases in the area have been observed since the advent of continuously profiling instruments in the late 1960's, the staircases are constantly advected and, modified by eddies and internal waves. The longevity of the individual layers has yet to be constrained. Schmitt et al. (1987) observed in their moored time series that four strong layers retained their identity for the entire eight months between the two
 C-SALT surveys. This suggests a minimum lifetime of approximately eight months. Several threads of evidence presented here strongly suggest that the feature observed toward the eastern end of seismic Line D2 is a thermohaline staircase. The CTD profile from HRP dive 125 deployed in 2001, co-located with Line D2, intersects the approximate location of the staircase imaged in 1998, but does not contain profiles with the characteristic step-like finestructure. Thus, the staircase had a lifetime of less than 3 years at this site.

#### 3.5 Weak turbulence

Thermohaline staircases are characterized by very low levels of viscous dissipation rate of turbulent kinetic energy ( $\epsilon$ ). During the C-SALT experiment, dissipation rate measured by microstructure measurements, averaged across the entire staircase, was close to the noise level of the measurements, of about ~  $10^{-10}$  W kg<sup>-1</sup> (Gregg and Sanford, 1987). Although  $\epsilon$  in a staircase is very low, for the C-SALT staircase, it was found to be eight times larger than predicted for  $\epsilon$  due only to internal waves (Gregg, 1989). This is likely due to additional dissipation associated with the buoyancy flux produced by salt fingers in the interfaces. Dissipation rate from internal waves can be inferred by the finescale parameterization that employs 10 m shear measurements (Gregg, 1989)



$$\epsilon_{\rm IW} = 7 \times 10^{-10} \left\langle \frac{N^2}{N_0^2} \right\rangle \left\langle \frac{S_{10}^4}{S_{\rm GM}^4} \right\rangle$$

Here  $S_{GM}$  and  $S_{10}$  are the Garrett-Munk (GM, Garrett and Munk, 1972) and observed, respectively, shear including all vertical wavelengths greater than 10 m,  $N_0 = 5.2 \times 10^{-3} \text{ s}^{-1}$  is the reference buoyancy frequency, *N* is the measured buoyancy frequency, and (.) indicates an average over space and time.

Here we apply Eq. 1 to HRP finescale velocity profiles in and outside of the staircase to show that internal-wave induced  $e_{IW}$  is anomalously low. We then compare  $e_{IW}$  to the observed dissipation rate,  $e_{obs}$ , measured by the microstructure sensors on HRP, to show that  $e_{obs} > e_{IW}$  in the staircase, consistent with Gregg and Sanford (1987). Finally, from an independent method, using spectral analysis of seismic data, we show that spectral signature of reflectors in the staircase is consistent with low  $e_{IW}$ .

Profiles of  $\epsilon_{obs}$  and  $\epsilon_{IW}$  for two HRP dives, one in the thermohaline staircase (123) and another outside (127) are contrasted in Fig. 10. In calculating  $\epsilon_{IW}$ , we follow Gregg

- <sup>15</sup> (1989) and obtain finescale shear components from linear fits over 10 m to the raw data and multiply by 2.11 to account for the attenuation of the first-difference filter. We average the 0.5-m vertical resolution observed dissipation rates to 10 m, to be consistent with  $\epsilon_{IW}$ . Outside the staircase, at dive 127, dissipation rate is significantly more energetic, explaining the absence of the staircase despite the low density ratio. At the depth
- <sup>20</sup> range corresponding to the staircase,  $e_{\rm IW}$  at dive 123 is suppressed by two orders of magnitude. Observed dissipation does not show this feature, likely owing to enhanced turbulence due to salt fingering. It should also be noted that assumptions involved both in the finescale parameterization and data processing of microstructure data are questionable in conditions favoring double diffusion. The agreement between the observed
- <sup>25</sup> and predicted dissipation rate for dive 127 is remarkable. Averaged between 400– 700 m depth for dive 127,  $\varepsilon_{IW} = 5.5 \times 10^{-9} \,\mathrm{W \, kg^{-1}}$ , identical to  $\varepsilon_{obs} = 6.3 \times 10^{-9} \,\mathrm{W \, kg^{-1}}$ within the measurement uncertainties. For dive 123,  $\varepsilon_{obs} = 2.9 \times 10^{-10} \,\mathrm{W \, kg^{-1}}$ , comparable to that in the C-SALT staircase (Gregg and Sanford, 1987).

7, 361–389, 2010

OSD

# Seismic imaging of a thermohaline staircase

I. Fer et al.





Another conclusion from the  $e_{IW}$  profile of dive 123 is that the internal wave field is significantly less energetic than the GM field. This is in agreement with Gregg (1989)

who found  $\left\langle \frac{S_{10}^4}{S_{GM}^4} \right\rangle$  of about 0.6 for the C-SALT staircase. Resulting dissipation rates are very low accordingly. Consistent with our measurements and C-SALT results, we

- <sup>5</sup> infer low internal wave signature in the seismic transect in the vicinity of the staircase. Spectral analysis of reflections from the western part of the line, between 50-150 km is shown in Fig. 11. Following Holbrook and Fer (2005), we compare ensemble-averaged horizontal wavenumber spectra of reflector displacement to the Garrett-Munk tow spectrum (GM, Garrett and Munk, 1972), as described in Katz and Briscoe (1979). The GM spectra are scaled by the survey mean  $N = 1.9 (\pm 0.28)$  cph between 400–1000 m depth, the typical range of the selected reflectors. In total 476 and 477 segments of 1600 m length were picked in the open ocean along Line D2, between 60–100 km and 110–150 km, respectively. The average spectrum from each set of ensembles, representative of the open ocean, follow the -2 slope of the GM spectrum and agree with
- the GM level within 95% confidence between 500–125 m wavelengths.

Vertical displacement variance is three times more energetic than GM at higher wavenumbers at scales smaller than 125 m, before flattening out as the ratio of signal to noise decreases. The relatively elevated spectral level at 1 km horizontal scale can be attributed to the Aves Ridge and variable local bathymetry. Within the thermo-

- haline staircase, 75 segments of 1600 m length are available for spectral analysis. The ensemble-averaged spectrum in the thermohaline staircase, however, contains lower variance, significant at 95% confidence, relative to the samples from the open ocean. In general, energy in the staircase does not compare well with and is significantly less energetic than the GM tow spectrum at scales less than 1 km. The spectral level at
- scales larger than 1 km suggest a background internal wave activity that might lead to weak turbulent fluxes; however, the existence of the regular structure in the staircase shows that double-diffusive fluxes must dominate.

# OSD 7, 361-389, 2010 Seismic imaging of a thermohaline staircase I. Fer et al. **Title Page** Introduction Abstract Conclusions References Tables Figures Back Close Full Screen / Esc Printer-friendly Version Interactive Discussion

#### 4 Conclusions

Our study indicates that the seismic reflection method is able to image the step-like structure of a thermohaline staircase. We present a seismic line from the Lesser Antilles which contains closely spaced reflections, horizontally coherent over 4 km, ap-

- <sup>5</sup> pearing clearly as high-amplitude interfaces separated by increasing distance with depth, from 19 to 25 m. The general area of the western tropical North Atlantic has been known to harbor staircases for at least the last 40 years. Synthetic modeling using the density and sound speed structure from a CTD containing the step-like structure of a thermohaline staircase indicates that the seismic reflection method is able to
- image it correctly and serves as validity for our observations. Reflections from the synthetic staircase are closely spaced with amplitudes comparable to those that arrive at the same times in the seismic data. Comparison of reflection coefficients from a strong thermohaline staircase sampled during the C-SALT experiment and those calculated from the seismic data indicate that they have similar spacing and magnitudes, i.e., the seismic line imported a strong stringer.
- <sup>15</sup> seismic line imaged a strong staircase.

Spectral analysis of reflectors indicates that the inferred internal wave level in the vicinity of the staircase is anomalously low, relative to adjacent measurements. A finescale parameterization applied to independent measurements of velocity profiles in and outside of the staircase confirm the weak internal wave field and very low internal wave induced dissipation within the staircase. Microstructure measurements show that the observed dissipation rates in the staircase are one order of magnitude less than those outside the staircase. Agreement between seismic and oceanographic data suggests that dissipation levels can be inferred from seismic sections.

A CTD profile taken in 2001 in the location of the staircase imaged in 1998 indicate that the layers are not permanent and have a lifetime of less than three years in this immediate area. Evidence gathered from a combination of seismic observations, modeling, finescale hydrography and currents, and microstructure measurements support the notion that legacy seismic data can be used to map thermohaline staircases.

### OSD

7, 361–389, 2010

# Seismic imaging of a thermohaline staircase

I. Fer et al.





With sufficiently tuned modern data, layer thickness and temperature jumps across interfaces can be inferred from the impedance contrasts and allow for diffusive flux estimates from widely-used parameterizations. Such structural and physical observations can then be compared for a greater understanding of finestructure and mixing in the global ocean.

*Acknowledgements.* This research was supported by NSF grant OCE-0221366 and ONR grant ONR-N000140410585 to Holbrook, NSF grant OCE-0647573 to Schmitt and the University of Wyoming Graduate School Women and Minority Fellowship to Nandi.

#### References

5

15

25

- Bangs, N.: Ewing Cruise EW9803, 15 March–6 April 1998, Structure tectonics and sediment flow through the Lesser Antilles Subduction Zone, Tech. rep., Institute og Geophysics, University of Texas, 1998. 365
  - Biescas, B., Sallarès, V., Pelegri, J. L., Machin, F., Carbonell, R., Buffett, G., Dañobeitia, J. J., and Calahorrano, A.: Imaging Meddy finestructure using multichannel seismic data, Geophys. Res. Lett., 35, L11609, doi:10.1029/2008GL033971, 2008. 364
  - Fer, I. and Holbrook, W. S.: Seismic reflection methods for study of the water column, in: Encylopedia of Ocean Sciences 2nd edn., edited by: Steele, J. H., Turekian, K. K., and Thorpe, S. A., Academic Press, Oxford, 2008. 364

Fortin, W. F. J. and Holbrook, W. S.: Sound speed requirements for optimal imaging of seismic

<sup>20</sup> oceanography data, Geophys. Res. Lett., 36, L00D01, doi:10.1029/2009gl038991, 2009. 367

Garrett, C. J. and Munk, W. H.: Space-time scales of internal waves, Geophys. Fluid Dyn., 3, 225–264, 1972. 374

Gregg, M. C.: Scaling turbulent dissipation in the thermocline, J. Geophys. Res., 94, 9686–9698, 1989. 372, 373, 374, 388

- Gregg, M. C. and Sanford, T. B.: Shear and turbulence in thermohaline staircases, Deep-Sea Res. A, 34, 1689–1696, 1987. 372, 373
- Holbrook, W., Páramo, P., Pearse, S., and Schmitt, R.: Thermohaline fine structure in an oceanographic front from seismic reflection profiling, Science, 301, 821–824, 2003. 364

#### OSD

7, 361–389, 2010

# Seismic imaging of a thermohaline staircase

I. Fer et al.



- Holbrook, W. S. and Fer, I.: Ocean internal wave spectra inferred from seismic reflection transects, Geophys. Res. Lett., 32, L15604, doi:10.1029/2005GL023733, 2005. 364, 368, 374
- Holbrook, W. S., Fer, I., and Schmitt, R. W.: Images of internal tides near the Norwegian continental slope, Geophys. Res. Lett., 36, L00D10, doi:10.1029/2009GL038909, 2009. 364
- 5 Katz, E. J. and Briscoe, M. G.: Vertical coherence of the internal wave field from towed sensors, J. Phys. Oceanogr., 9, 518–530, 1979. 374
  - Kelley, D. E.: Effective diffusivities within oceaninc thermohaline staircases, J. Geophys. Res., 89, 10484–10488, 1984. 362
  - Kelley, D. E., Fernando, H. J. S., Gargett, A. E., Tanny, J., and Özsoy, E.: The diffusive regime of double-diffusive convection, Prog. Oceanogr., 56, 461–481, 2003. 363
- Krahmann, G., Brandt, P., Klaeschen, D., and Reston, T.: Mid-depth internal wave energy off the Iberian Peninsula estimated from seismic reflection data, J. Geophys. Res., 113, C12016, doi:10.1029/2007JC004678, 2008. 364

10

Nakamura, Y., Noguchi, T., Tsuji, T., Itoh, S., Niino, H., and Matsuoka, T.: Simultaneous seismic

- reflection and physical oceanographic observations of oceanic fine structure in the Kuroshio extension front, Geophys. Res. Lett., 33, L23605, doi:10.1029/2006GL027437, 2006. 364 Nandi, P., Holbrook, W. S., Pearse, S., Paramo, P., and Schmitt, R. W.: Seismic reflection
  - imaging of water mass boundaries in the Norwegian Sea, Geophys. Res. Lett., 31, L23311, doi:10.1029/2004GL021325, 2004. 364
- Pinheiro, L. M., Song, H., Ruddick, B., Dubert, J., Ambar, I., Mustafa, K., and Bezerra, R.: Detailed 2-D imaging of the Mediterranean outflow and meddies off W Iberia from multichannel seismic data, J. Marine Syst., 79, 89–100, 2010. 364
  - Polzin, K. L. and Montgomery, E. T.: Microstructure Profiling with the High Resolution Profiler, Tech. rep., Woods Hole Oceanographic Institution, 1998. 366
- Ruddick, B., Song, H., Dong, C., and Pinheiro, L.: Water column seismic images as maps of temperature gradient, Oceanography, 22, 192–205, 2009. 364, 367
  - Sallarès, V., Biescas, B., Buffett, G., Carbonell, R., Dañobeitia, J. J., and Pelegri, J. L.: Relative contribution of temperature and salinity to ocean acoustic reflectivity, Geophys. Res. Lett., 36, L00D06, doi:10.1029/2009gl040187, 2009. 364, 367
- Schmitt, R. W.: Form of the temperature-salinity relationship in the central water evidence for double-diffusive mixing, J. Phys. Oceanogr., 11, 1015–1026, 1981. 363, 370
  Schmitt, R. W.: On the density ratio balance in the central water, J. Phys. Oceanogr., 20, 900–906, 1990. 363





- Schmitt, R. W.: Observational and laboratory insights into salt finger convection, Prog. Oceanogr., 56, 419–433, 2003. 363, 369
- Schmitt, R. W., Perkins, H., Boyd, J. D., and Stalcup, M. C.: C-SALT An investigation of the thermohaline staircase in the western tropical North-Atlantic, Deep-Sea Res. A, 34, 1655–

<sup>5</sup> 1665, 1987. 363, 365, 366, 371, 372, 379

Schmitt, R. W., Toole, J. M., Koehler, R. L., Mellinger, E. C., and Doherty, K. W.: The Development of a Fine- and Microstructure Profiler, J. Atmos. Ocean. Technol., 5, 484–500, 1988. 366

Schmitt, R. W., Ledwell, J. R., Montgomery, E. T., Polzin, K. L., and Toole, J. M.: Enhanced

- diapycnal mixing by salt fingers in the thermocline of the tropical Atlantic, Science, 308, 685–688, 2005. 363
  - St. Laurent, L. C. and Schmitt, R. W.: The contribution of salt fingers to vertical mixing in the North Atlantic tracer release experiment, J. Phys. Oceanogr., 29, 1404–1424, 1999. 363
  - Stern, M. E.: The "salt-fountain" and thermohaline convection, Tellus A, 12, 172–175, 1960. 363
- 15
  - Sundfjord, A., Fer, I., Kasajima, Y., and Svendsen, H.: Observations of turbulent mixing and hydrography in the marginal ice zone of the Barents Sea, J. Geophys. Res., 112, C05008, doi:10.1029/2006JC003524, 2007. 363

Turner, J. S.: Buoyancy Effects in Fluids, Cambridge University Press, New York, 1973. 362

20 Warner, M.: Absolute reflection coefficients from deep seismic reflections, Tectonophysics, 173, 15–23, 1990. 367

Widess, M.: How thin is a thin bed?, Geophysics, 38, 1176–1180, 1973. 366

Zhang, J. and Schmitt, R. W.: The impact of salt fingering on the thermohaline circulation under mixed boundary conditions, J. Phys. Oceanogr., 30, 1223–1231, 2000. 363

OSD	
7, 361–389, 2010	
Seismic imaging of a thermohaline staircase I. Fer et al.	
Title Page	
Abstract	Introduction
Conclusions	References
Tables	Figures
I	▶1
•	
Back	Close
Full Screen / Esc	
Printer-friendly Version	
Interactive Discussion	





**Fig. 1.** Bathymetric map of the study area near the Lesser Antilles in the Caribbean Sea. Lower panel is a blow-up of the study region marked by the rectangle in the upper panel. Line D2 (black) is the transect of the 1998 seismic reflection survey. The stations where the high-resolution profiler (HRP) was deployed in 2001 are marked by red stars (dives 123 to 128). Dive 123 (easternmost) is used in the synthetic modeling (Sect. 2.3). Dive 125, at the eastern end of Line D2, is used to constrain the longevity of the layers. The spatial extent of strong staircases identified during the 1985 C-SALT experiment is shown for the spring (magenta) and fall (dashed green) surveys together with the C-SALT tow-yo location (diamond) (Schmitt et al., 1987).







**Fig. 2.** Vertically exaggerated seismic image of Line D2, collected from West to East across the Caribbean Sea with the shelf of Guadeloupe on the left (masked white). The thermohaline staircase is the high amplitude reflective package (inset) visible from about 200–212 km at depths between 550 and 700 m. These regular, uniformly spaced, banded layers are unique to this part of the section.



OSD





OSD 7, 361-389, 2010 Seismic imaging of a thermohaline staircase I. Fer et al. **Title Page** Introduction Abstract Conclusions References Tables Figures Back Close Full Screen / Esc Printer-friendly Version Interactive Discussion



**Fig. 3.** Temperature (red), salinity (blue) and potential density anomaly ( $\sigma_{\theta}$ , referenced to zero pressure, black) measured by HRP dive 125 near the eastern end of the seismic profile (Fig. 1). Water masses characteristic of this region are the Caribbean Surface Water with a salinity lower than 35.5 at depths lower than 50 m, Subtropical Underwater at depths between 50–200 m and a salinity maximum exceeding 37, and Antarctic Intermediate Water at depths between 600–1000 m and a salinity minimum of around 34.7.



**Fig. 4.** Profiles of (a) temperature and (b) density ratio,  $R_{\rho}$  inferred from the HRP dives deployed in 2001. Dive 123 indicates data upon a synthetic seismic study was based. The temperature scale is correct for the leftmost CTD. Each subsequent profile is offset by 2°C, shown in alternating red and black color. Density ratio profiles are offset and colored accordingly with  $R_{\rho} = 1$  and 2 indicated by vertical lines.  $R_{\rho} > 2$  are masked for clarity.









Full Screen / Esc

Printer-friendly Version

Interactive Discussion



**Fig. 6.** Profiles of **(a)** temperature and salinity and **(b)** density ratio,  $R_{\rho}$  and sound speed in the staircase (HRP dive 123). Sound speed and in-situ density profiles from this dive are used for the synthetic analysis.

![](_page_23_Figure_2.jpeg)

![](_page_24_Figure_0.jpeg)

**Fig. 7.** Reflection coefficients calculated from a C-SALT CTD tow-yo at a strong, well-defined thermohaline staircase. Peaks in reflection coefficient correspond to sharp changes in sound speed. Values at the high-gradient layers are larger than background noise.

![](_page_24_Picture_2.jpeg)

Printer-friendly Version

Interactive Discussion

![](_page_25_Figure_0.jpeg)

**Fig. 8.** Reflection coefficients calculated from a section of a 1 km near-offset time-migrated seismic stack, centered on the thermohaline staircase. Values at the high-gradient layers are larger than background noise and show a regular, lateral coherence throughout the profile. High values at 1000 and 4000 m correspond to errors caused by a diffraction in the sea floor, only partially corrected by the migration, and extremely low sea floor and multiple amplitudes respectively.

### OSD 7, 361-389, 2010 Seismic imaging of a thermohaline staircase I. Fer et al. **Title Page** Introduction Abstract Conclusions References Tables Figures Back Close Full Screen / Esc **Printer-friendly Version** Interactive Discussion

![](_page_25_Picture_3.jpeg)

![](_page_26_Figure_0.jpeg)

**Fig. 9.** Unstacked synthetic seismic results using the CTD profile from HRP dive 123 east of Line D2 (Fig. 1). The direct arrival appears as large amplitude linear reflections starting at the sea surface. Reflections from synthetic sound velocity and density structure calculated from the CTD are seen as hyperbolic horizons starting at about 200 m at zero offset. The synthetic staircase is imaged as the next strongest coherent packet of four reflections with the same moveout, visible at higher offsets. The red lines in the inset identify staircase reflections. Note that only depths at zero offset correspond to depths on a stacked section.

#### OSD

7, 361–389, 2010

# Seismic imaging of a thermohaline staircase

I. Fer et al.

![](_page_26_Figure_6.jpeg)

![](_page_26_Picture_7.jpeg)

![](_page_27_Figure_0.jpeg)

![](_page_27_Figure_1.jpeg)

388

![](_page_27_Figure_2.jpeg)

![](_page_27_Picture_3.jpeg)

![](_page_28_Figure_0.jpeg)

**Fig. 11.** Ensemble-averaged vertical displacement spectra of selected horizons in the vicinity of the thermohaline staircase (black) and in the open ocean (red and blue). All spectra are scaled by the average buoyancy frequency within the depth span of the horizons. Dashed line shows the Garrett-Munk tow (Katz and Briscoe, 1979) spectrum representing the average background internal wave energy for the average buoyancy frequency (N = 1.9 cph), enveloped by  $\pm 0.28$  cph (gray shading, barely distinguishable from the dashed curve). 95% confidence intervals (CI) are indicated for 160 and 25 degrees of freedom, respectively, for the open ocean and staircase spectra, assuming that every 6th reflector is de-correlated vertically. The energy level in the staircase is anomalously low whereas those derived from other horizons are collapsed by the buoyancy frequency and scale to a level above the Garrett-Munk spectra.

![](_page_28_Figure_2.jpeg)

![](_page_28_Picture_3.jpeg)