



Frictional interactions between tidal constituents in tide-dominated estuaries

Huayang Cai¹, Marco Toffolon², Hubert H. G. Savenije³, Qingshu Yang¹, and Erwan Garel⁴

¹Institute of Estuarine and Coastal Research, School of Marine Sciences, Sun Yat-sen University, Guangzhou 510275, China

²Department of Civil, Environmental and Mechanical Engineering, University of Trento, Italy

³Department of Water Management, Faculty of Civil Engineering and Geosciences, Delft University of Technology, Netherlands

⁴Centre for Marine and Environmental Research (CIMA), University of Algarve, Faro, Portugal

Correspondence to: Erwan Garel (egarel@ualg.pt)

Abstract. When different tidal constituents propagate along an estuary, they interact because of the presence of nonlinear terms in the hydrodynamic equations. In particular, due to the quadratic velocity in the friction term, the effective friction experienced by both the predominant and the minor tidal constituents is enhanced. We explore the underlying mechanism with a simple conceptual model by utilizing Chebyshev polynomials, enabling the effect of the velocities of the tidal constituents to be summed in the friction term and, hence, the linearized hydrodynamic equations to be solved analytically in a closed form. An analytical model is adopted for each single tidal constituent with a correction factor to adjust the linearized friction term, accounting for the mutual interactions between the different tidal constituents by means of an iterative procedure. The proposed method is applied to the Guadiana (southern Portugal-Spain border) and the Guadalquivir (Spain) estuaries for different tidal constituents (M_2 , S_2 , N_2 , O_1 , K_1) imposed independently at the estuary mouth. The analytical results appear to agree very well with the observed tidal amplitudes and phases of the different tidal constituents.

1 Introduction

Numerous studies have been conducted in recent decades to model tidal wave propagation along an estuary since an understanding of tidal dynamics is essential for exploring the influence of human-induced (such as dredging for navigational channels) or natural (such as global sea level rises) interventions on estuarine environments (Schuttenaars et al., 2013; Winterwerp et al., 2013). Analytical models are invaluable tools and have been developed to study the basic physics of tidal dynamics



20 in estuaries; for instance, to examine the sensitivity of tidal properties (e.g., tidal damping or wave speed) to change in terms of external forcing (e.g., spring–neap variations of amplitude) and geometry (e.g., depth or channel length). However, most analytical solutions developed to date, which make use of the linearized Saint-Venant equations, can only deal with one predominant tidal constituent (e.g., M_2), which prevents consideration of the nonlinear interactions between different tidal

25 constituents. The underlying problem is that the friction term in the momentum equation follows a quadratic friction law, which causes a nonlinear behavior causing tidal asymmetry as tide propagates upstream. If the friction law were linear, one would expect that the effective frictional effect for different tidal constituents (e.g., M_2 and S_2) could be computed independently (Pingree, 1983).

To explore the interaction between different constituents of the tidal flow, the quadratic velocity
30 $u|u|$ (where u is the velocity) is usually approximated by a truncated series expansion, such as a Fourier expansion (Proudman, 1953; Dronkers, 1964; Le Provost, 1973; Pingree, 1983; Fang, 1987; Inoue and Garrett, 2007). If the tidal current is composed of one dominant constituent and a much smaller second constituent, it has been shown by many researchers (Jeffreys, 1970; Heaps, 1978; Prandle, 1997) that the weaker constituent is acted on by up to 50% more friction than that of the
35 dominant constituent. However, this requires the assumption of a very small value of the ratio of the magnitudes of the weaker and dominant constituents, which indicates that this is only a first-order estimation. Later, some researchers have extended the analysis to improve the accuracy of estimates and to allow for more than two constituents (Pingree, 1983; Fang, 1987; Inoue and Garrett, 2007). Pingree (1983) investigated the interaction between M_2 and S_2 tides, resulting in a second-order
40 correction of the effective friction coefficient acting on the predominant M_2 tide and a fourth-order value for the weaker S_2 constituent of the tide. Fang (1987) derived exact expressions of the coefficients of the Fourier expansion of $u|u|$ for two tidal constituents but did not provide exact solutions for the case of three or more constituents. Later, Inoue and Garrett (2007) used a novel approach to determine the Fourier coefficients of $u|u|$, which allows the magnitude of the effective friction
45 coefficient to be determined for many tidal constituents. For the general two-dimensional tidal wave propagation, the expansion of quadratic bottom friction using a Fourier series was first proposed by Le Provost (1973) and subsequently applied to spectral models for regional tidal currents (Le Provost et al., 1981; Le Provost and Fornerino, 1985; Molines et al., 1989). Building on the previous work by Le Provost (1973), the importance of quadratic bottom friction in tidal propagation and damping was
50 discussed by Kabbaj and Le Provost (1980) and reviews of friction term in models were presented by Le Provost (1991).

In contrast, as noted by other researchers (Doodson, 1924; Dronkers, 1964; Godin, 1991, 1999), the quadratic velocity $u|u|$ is, mathematically, an odd function, and it is possible to approximate it by using a two- or three-term expression, such as $\alpha u + \beta u^3$ or $\alpha u + \beta u^3 + \xi u^5$, where α , β , and ξ
55 are suitable numerical constants. The linear term αu represents the linear superposition of different constituents, while the nonlinear interaction is attributed to a cubic term βu^3 and a fifth-order term



ξu^5 . It is to be noted that such a method has the advantage of keeping the hydrodynamic equations resolvable in a closed form (Godin, 1991, 1999).

In this paper, a conceptual analytical model is presented to understand the propagation of different 60 tidal constituents that one might wish to treat independently. The key lies in the treatment of the quadratic velocity in the friction term. The model has subsequently been applied to the Guadiana and the Guadalquivir estuaries in southern Iberian Peninsula, for which case the mutual interaction between the predominant M_2 tidal constituent and other tidal constituents (e.g., S_2 , N_2 , O_1 , K_1) is explored.

65 2 Materials and methods

2.1 Hydrodynamic model

We are considering a semi-closed estuary that is forced by one predominant tidal constituent (e.g., M_2) with the tidal frequency $\omega = 2\pi/T$, where T is the tidal period. As the tidal wave propagates into the estuary, it has a wave celerity of water level c_A , a wave celerity of velocity c_V , an amplitude 70 of tidal elevation η , a tidal velocity amplitude v , a phase of water level ϕ_A , and a phase of velocity ϕ_V . The length of the estuary is indicated by L_e .

The geometry of a semi-closed estuary is shown in Figure 1, where x is the longitudinal coordinate, which is positive in the landward direction, and z is the free surface elevation. The tidally averaged cross-sectional area \bar{A} and width \bar{B} are assumed to be exponentially convergent in the 75 landward direction, which can be described by

$$\bar{A} = \bar{A}_0 \exp(-x/a), \quad (1)$$

$$\bar{B} = \bar{B}_0 \exp(-x/b), \quad (2)$$

where \bar{A}_0 and \bar{B}_0 are the respective values at the estuary mouth (where $x=0$), and a and b are the 80 convergence lengths of cross-sectional area and width, respectively. We also assume a rectangular cross-section, from which it follows that the tidally averaged depth is given by $\bar{h} = \bar{A}/\bar{B}$. The possible influence of storage area is described by the storage width ratio r_S , defined as the ratio of the storage width to the tidally averaged width (i.e., $r_S = \bar{B}_S/\bar{B}$).

With the above assumptions, the one-dimensional continuity equation reads

$$85 \quad r_S \frac{\partial h}{\partial t} + u \frac{\partial h}{\partial x} + h \frac{\partial u}{\partial x} + \frac{h u}{\bar{B}} \frac{d\bar{B}}{dx} = 0, \quad (3)$$

where t is the time and h the instantaneous depth. Assuming negligible density effects, the one-dimensional momentum equations can be cast as follows

$$\frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + g \frac{\partial z}{\partial x} + \frac{g u |u|}{K^2 h^{4/3}} = 0, \quad (4)$$

where g is the acceleration due to gravity and K is the Manning-Strickler friction coefficient.



90 In order to obtain an analytical solution, we assume that the tidal amplitude is small with respect to the mean depth and follow Toffolon and Savenije (2011) to derive the linearized solution of the system of Eqs. (3) and (4). However, different from the standard linear solutions, we will retain the mutual interaction among different harmonics originated by the nonlinear frictional term, which contains two sources of nonlinearity: the quadratic velocity $u|u|$ and the variable depth at the denominator. While we neglect the latter factor, consistent with the assumption of small tidal amplitude, we will exploit Chebyshev polynomials to represent the harmonic interaction in the quadratic velocity (see Section 3.1). For sake of clarity, we report here the linearized version of the momentum equation

$$\frac{\partial u}{\partial t} + g \frac{\partial z}{\partial x} + \kappa u|u| = 0, \quad (5)$$

100 and the friction coefficient

$$\kappa = \frac{g}{K^2 \bar{h}^{4/3}}. \quad (6)$$

Toffolon and Savenije (2011) demonstrated that the tidal hydrodynamics in a semi-closed estuary are controlled by a few dimensionless parameters that depend on geometry and external forcing (for detailed information about analytical solutions for tidal hydrodynamics, readers can refer to 105 Appendix A). These parameters are defined in Table 1 and can be interpreted as follows.

The independent dimensionless parameters are: ζ_0 is the dimensionless tidal amplitude (the subscript 0 indicating the seaward boundary condition); γ is the estuary shape number (representing the effect of cross-sectional area convergence); χ_0 is the friction number (describing the role of the frictional dissipation); L_e^* is the dimensionless estuary length. The dimensional quantities used in 110 the definition of the dimensionless parameters are: η_0 is the tidal amplitude at the seaward boundary; $c_0 = \sqrt{gh}/r_S$ is the frictionless wave celerity in a prismatic channel; $L_0 = c_0/\omega$ is the tidal length scale related to the frictionless tidal wave length by a factor 2π .

The main dependent dimensionless parameters are also presented in Table 1, including: ζ is the actual tidal amplitude; χ is the actual friction number; μ is the velocity number (the ratio of the actual 115 velocity amplitude to the frictionless value in a prismatic channel); λ_A and λ_V are, respectively, the celerity for elevation and velocity (the ratio between the frictionless wave celerity in a prismatic channel and actual wave celerity); δ_A and δ_V are, respectively, the amplification number for elevation and velocity (describing the rate of increase, δ_A (or δ_V) > 0 , or decrease, δ_A (or δ_V) < 0 , of the wave amplitudes along the estuary axis); $\phi = \phi_V - \phi_A$ is the phase difference between the phases of 120 velocity and elevation.

It is important to remark that several nonlinear terms are present both in the continuity and in the momentum equations (Parker, 1991), which are responsible, for instance, of the internal generation of over tides (e.g., M_4). In this approximated approach, we disregard them and focus exclusively on the mutual interaction among the external tidal constituents mediated by the quadratic velocity



125 dependence in the frictional term. In fact, it crucially affects the propagation of the tidal waves associated with the different constituents that are already present in the tidal forcing at the estuary mouth.

2.2 Study areas

Both the Guadiana and the Guadalquivir estuaries are located in the southwest part of the Iberian Peninsula. These systems are good candidates for the application of a 1D hydrodynamic model of tidal propagation. Both estuaries are featured with a simple geometry, consisting of a single, narrow and moderately deep channel with relatively smooth bathymetric variations. Moreover, their tidal prism exceeds their average freshwater inputs by several orders of magnitude due to strong regulation by dams. Under these largely predominant low river discharge conditions, both estuaries 130 are well-mixed, and the water circulation is mainly driven by tides.

The Guadiana estuary, at the southern border between Spain and Portugal, connects the Guadiana River to the Gulf of Cadiz. Tidal water level oscillations are observed along the channel until a weir located 78 km upstream of the river mouth (Garel et al., 2009). Both the cross-sectional area and the channel width are convergent and can be described by an exponential function, with convergence 135 lengths of $a=31$ km and $b=38$ km, respectively (Figure 2). The flow depth is generally between 4 m and 8 m, with a mean depth of about 5.5 m (Garel, 2017).

The tidal dynamics in the Guadiana estuary are derived from records obtained using eight pressure transducers deployed for a period of 2 months (31 July to 25 September 2015) approximately every 10 km along the estuary (from the mouth to ~ 70 km upstream). For each station, the amplitude 140 and phase of elevation of the tidal constituents were obtained from standard harmonic analysis of the observed pressure records using the “t-tide” Matlab toolbox (Pawlowicz et al., 2002). The harmonic results are displayed in Table 2. Near the mouth, the largest diurnal (K_1), semi-diurnal (M_2) and quarter-diurnal (M_4) frequencies are similar to those previously reported at the same location based on pressure records taken over ~ 9 months (see Garel and Ferreira, 2013). In particular, the 145 value $(\eta_{K_1} + \eta_{O_1})/(\eta_{M_2} + \eta_{S_2})$ is less than 0.1 at the sea boundary, which indicates that the tide is dominantly semi-diurnal.

The Guadalquivir estuary is located in southern Spain, at ~ 100 km to the east of the Guadiana River mouth. The estuary has a length of 103 km starting from the mouth at Sanlucar de Barrameda to the Alcala del Rio dam. The geometry of the Guadalquivir estuary can be approximated by 150 exponential functions with convergence length of $a=60$ km for the cross-sectional area and $b=66$ km for the width (see Diez-Minguito et al., 2012). The flow depth is more or less constant (7.1 m).

Tidal dynamics along the Guadalquivir estuary was analysed by Diez-Minguito et al. (2012) based on harmonic analyses of field measurements collected from June to December 2008. The amplitude and phase of tidal constituents near the mouth are highly similar to those at the entrance 155 of the Guadiana estuary (Table 2), producing a semi-diurnal and mesotidal signal with a mean spring



tidal range of 3.5 m. In this paper, the tidal observations of the Guadalquivir estuary are directly taken from Diez-Minguito et al. (2012).

3 Conceptual model

3.1 Representation of quadratic velocity $u|u|$ using Chebyshev polynomials approach

165 The Chebyshev polynomials can be used to approximate the quadratic dependence of the friction term on the velocity, $u|u|$. Adopting a two-term approximation, it is known that (Godin, 1991, 1999)

$$u|u| = \hat{v}^2 \left[\alpha \left(\frac{u}{\hat{v}} \right) + \beta \left(\frac{u}{\hat{v}} \right)^3 \right], \quad (7)$$

where \hat{v} is the sum of the amplitudes of all the harmonic constituents. The Chebyshev coefficients 170 were determined as $\alpha = 16/(15\pi)$, and $\beta = 32/(15\pi)$ (Godin, 1991, 1999). It is important to note that, unlike series developments (e.g., Fourier expansion), the Chebyshev coefficients α and β vary with the number of terms that are used in the development. Godin (1991) already showed that a two-term approximation (such as Eq. 7) is adequate to satisfactorily account for the friction.

For a single harmonic

$$175 \quad u = v_1 \cos(\omega_1 t), \quad (8)$$

where v_1 is the velocity amplitude and ω_1 its frequency, Eq. (7) can be expressed by exploiting standard trigonometric relations as

$$u|u| \cong v_1^2 \left[\frac{8}{3\pi} \cos(\omega_1 t) + \frac{8}{15\pi} \cos(3\omega_1 t) \right]. \quad (9)$$

Focusing only on the original harmonic constituent leads to

$$180 \quad u|u| \cong \frac{8}{3\pi} v_1^2 \cos(\omega_1 t), \quad (10)$$

which coincides exactly with Lorentz's classical linearization (Lorentz, 1926) or a Fourier expansion of $u|u|$ (Proudman, 1953).

Considering a second tidal constituent, the velocity is given by

$$u = v_1 \cos(\omega_1 t) + v_2 \cos(\omega_2 t) = \hat{v} [\varepsilon_1 \cos(\omega_1 t) + \varepsilon_2 \cos(\omega_2 t)], \quad (11)$$

185 where v_2 and ω_2 are the amplitude and frequency of the second constituent, $\varepsilon_1 = v_1/\hat{v}$ and $\varepsilon_2 = v_2/\hat{v}$ are the ratios of the amplitudes to that of the maximum possible velocity $\hat{v} = v_1 + v_2$. Note that the possible phase lag between the two constituents is neglected assuming a suitable time shift (Inoue and Garrett, 2007). In this case, the truncated Chebyshev polynomials approximation of $u|u|$ (focusing on two original tidal constituents) is expressed as (see also Godin, 1999)

$$190 \quad u|u| \cong \frac{8}{3\pi} \hat{v}^2 [F_1 \varepsilon_1 \cos(\omega_1 t) + F_2 \varepsilon_2 \cos(\omega_2 t)], \quad (12)$$



with

$$F_1 = \frac{3\pi}{8} \left[\alpha + \beta \left(\frac{3}{4}\varepsilon_1^2 + \frac{3}{2}\varepsilon_2^2 \right) \right] = \frac{1}{5}(2 + 3\varepsilon_1^2 + 6\varepsilon_2^2) = \frac{1}{5}(8 + 9\varepsilon_1^2 - 12\varepsilon_1), \quad (13)$$

$$F_2 = \frac{3\pi}{8} \left[\alpha + \beta \left(\frac{3}{4}\varepsilon_2^2 + \frac{3}{2}\varepsilon_1^2 \right) \right] = \frac{1}{5}(2 + 3\varepsilon_2^2 + 6\varepsilon_1^2) = \frac{1}{5}(5 + 9\varepsilon_1^2 - 6\varepsilon_1), \quad (14)$$

195 where F_1 and F_2 represent the effective friction coefficients caused by the nonlinear interactions between tidal constituents. The last equality in Eqs. (13) and (14) is due to the fact that $\varepsilon_1 + \varepsilon_2 = 1$.

For illustration, approximations using Eqs. (7) and (12) for a typical tidal current with $\varepsilon_1 = 3/4$ and $\varepsilon_2 = 1/4$ are displayed in Figure 3 for the case of two tidal constituents. It can be seen that the Chebyshev polynomials approximation (Eq. 7) matches the nonlinear quadratic velocity well, while 200 Eq. (12), retaining only the original frequencies (ω_1 and ω_2), is still able to approximately capture the first-order trend of the quadratic term.

It can be seen from Eqs. (13) and (14) that when $\varepsilon_2 \ll 1$ (hence, $\varepsilon_1 \simeq 1$ for the dominant tidal constituent), $F_1 \simeq 1$, $F_2 \simeq 1.6$, thus the weaker constituent experiences proportionately 60% more friction than the dominant constituent, which is slightly larger than the classical result of 50% more 205 friction for the weaker tidal constituent. Figure 4 shows the solutions of effective friction coefficients F_1 and F_2 as a function of ε_1 for the case of two constituents. As expected, we see a symmetric response of these coefficients in the function of ε_1 since $\varepsilon_1 + \varepsilon_2 = 1$. Specifically, we note that the effective friction coefficient F_1 reaches a minimum when $\varepsilon_1 = 2/3$, when the velocity amplitude of the dominant constituent is twice larger than the weaker constituent.

210 Similarly, we are able to extend the same approach to the case of a generic number n of astronomical tidal constituents (e.g., K₁, O₁, M₂, S₂, N₂)

$$u = \sum_{i=1}^n v_i \cos(\omega_i t) = \hat{v} \sum_{i=1}^n \varepsilon_i \cos(\omega_i t), \quad (15)$$

in which the subscript i represents the i -th tidal constituent. Considering only the original tidal constituents, the quadratic velocity can be approximated as

$$215 u|u| \cong \frac{8}{3\pi} \hat{v}^2 \sum_{i=1}^n F_i \varepsilon_i \cos(\omega_i t), \quad (16)$$

and the general expression for the effective friction coefficients of j -th tidal constituents is given by

$$F_j = \frac{3\pi}{8} \left\{ \alpha + \beta \left[\sum_{i=1, i \neq j}^n \frac{3}{2}\varepsilon_i^2 - \frac{3}{4}\varepsilon_j^2 \right] \right\} = \frac{1}{5} \left(2 + 3\varepsilon_j^2 + \sum_{i=1, i \neq j}^n 6\varepsilon_i^2 \right). \quad (17)$$

We provide the complete coefficients for the cases of one to three constituents in Appendix B.

3.2 Effective friction in the momentum equation

220 For a single tidal constituent $u = v_1 \cos(\omega_1 t)$, the quadratic velocity term $u|u|$ is often approximated by adopting Lorentz's linearization equation (Eq. 10) and thus the friction term in Eq. (5) becomes

$$\kappa u|u| = \left(\kappa \frac{8}{3\pi} v_1 \right) u = r u, \quad (18)$$



which is the “standard” case for a monochromatic wave, i.e. when we only deal with a predominant tidal constituent (e.g., M_2).

225 For illustration of the method, we consider a tidal current that is composed of one dominant constituent (e.g., M_2 with velocity u_1) and a weaker constituent (e.g., S_2 with velocity u_2), which is a simple but important example in estuaries, i.e., $u = u_1 + u_2$. In this case, combination of Eq. (5) and the Chebyshev polynomials expansion of $u|u|$ (Eq. 12) yields

$$\frac{\partial u_1}{\partial t} + \frac{\partial u_2}{\partial t} + g \frac{\partial z_1}{\partial x} + g \frac{\partial z_2}{\partial x} + \kappa \frac{8}{3\pi} \hat{v} (F_1 u_1 + F_2 u_2) = 0, \quad (19)$$

230 where z_1 is the free surface elevation for the dominant constituent and z_2 for the secondary constituent. Exploiting the linearity of Eq. (19), we can solve the two problems independently. As a result, we see that the actual friction term that is felt in Eq. (19) is different from that would be felt by the single constituent alone (Eq. 18).

Introducing a general form of the linearized momentum equation for the generic i -th constituent

$$235 \quad \frac{\partial u_i}{\partial t} + g \frac{\partial z_i}{\partial x} + f_i r_i u_i = 0, \quad (20)$$

with

$$r_i = \kappa \frac{8}{3\pi} v_i, \quad (21)$$

as in the standard case, we see that the effective friction term contains a correction factor

$$f_i = \frac{F_i}{\varepsilon_i}, \quad (22)$$

240 through the coefficient F_i . Since the ratio ε_i can be quite small for a weaker constituent, the friction actually felt can be significantly stronger.

4 Results

4.1 Hydrodynamic modeling incorporating the friction correction factor

If there are many tidal constituents, then the friction experienced by one is affected by the others.

245 As suggested by our conceptual model, the mutual effects can be incorporated by using the friction correction factor f_n defined in Eq. (22) if the other (weaker) constituents are treated in the same way as the predominant constituent. As a result, the friction number χ_n for each tidal constituent can be modified as

$$\chi_n = f_n \chi, \quad (23)$$

250 where χ is the friction number (see definition in Table 1) experienced if only a single tidal constituent is considered.



We note that the modified friction number χ_n in Eq. (23) contains the friction coefficient K . In many applications, K is calibrated separately for each tidal constituent to account for the different friction exerted due to the combined tide, either changing K directly or through calibration of the 255 different correction friction factors f_n (see, e.g., Cai et al., 2015, 2016). The current study aims at avoiding the need to adjust K individually, so that only a single value of K can be calibrated, which is based on the physical consideration that friction mostly depends on bottom roughness, and the other factors (tide interaction) are to be correctly modelled.

4.2 Procedure to study the propagation of the different constituents

260 With a hydrodynamic model for a single constituent (see Appendix A), an iterative procedure can be designed to study the propagation of the different constituents by calibrating a single value of the Manning-Strickler friction parameter K . The flow chart illustrating the computation process is presented in Figure 5. Initially, we assume the friction correction factor $f_i=1$ for each tidal constituent, and compute the first tentative values of velocity amplitude v_i along the channel using the hydrodynamic model. This allows defining \hat{v} and, hence, ε_i . Taking into account the frictional interaction between tidal constituents, the revised f_i is calculated using Eqs. (17) and (22). Subsequently, using the updated f_i , the new velocity amplitude v_i along the channel can be computed using the hydrodynamic model. This process is repeated until the result is stable. In this paper, two examples of Matlab scripts are provided together with the observed tidal data in the Guadiana and Guadalquivir 270 estuaries (see Supporting Information).

It is worth stressing that the single constituents are not calibrated independently, as was done in previous analyses (e.g., Cai et al., 2015). Conversely, only a single friction parameter, K , is calibrated or estimated based on the physical knowledge of the system (bed roughness). This feature represents a major advantage of the proposed method because the frictional interaction is modelled 275 in mechanistic terms using Eq. (22).

4.3 Application to the Guadiana and Guadalquivir estuaries

In this study, the analytical model for a semi-closed estuary presented in Section 2.1 was applied to the Guadiana and Guadalquivir estuaries to reproduce the correct tidal behavior for different tidal constituents. The analytical results were compared with observed tidal amplitude η and associated 280 phase of elevation ϕ_A .

The morphology of the Guadiana estuary was represented in the model with a constant depth (5.5 m), an exponentially converging width (length scale, 38 km) and a constant storage ratio of 1 representative of the limited salt marsh areas (about 20 km², see Garel (2017)). The Manning-Strickler friction coefficient ($K = 42 \text{ m}^{1/3}\text{s}^{-1}$) was determined by calibrating the model outputs 285 (obtained using the iterative procedure presented in section 4.2) with observations. It can be seen from Figure 6 that the computed tidal amplitude and phase of elevation are in good agreement with



the observed values for different tidal constituents in the Guadiana estuary. The N_2 amplitude is slightly overestimated in the central part of the estuary, which may suggest that the harmonic analysis has some difficulties to resolve this constituent in relation to the length of the considered time series
290 (54 days). In support, the N_2 amplitude (0.16 m) from a longer time series (85 days) collected in 2017 at 58 km from the mouth matches better the model output, while results for other constituents are similar in 2015 and 2017 (Garel, unpublished data). Otherwise, the correspondence is poorest for the semi-diurnal constituents at the most upstream station, owing to truncation of the lowest water levels by a sill located at about 65 km from the river mouth (Garel, 2017). Table 3 displays the mean
295 friction correction coefficient f obtained from the iterative procedure to account for the nonlinear interaction between different tidal constituents. In particular, the mean friction correction factors f for the minor constituents S_2 , N_2 , O_1 , and K_1 are 4.6, 8.1, 41.1, and 49.8, respectively.

To understand the tidal dynamics between different tidal constituents along the Guadiana estuary, the longitudinal variations of the tidal damping/amplification number δ_A and celerity number λ_A (see
300 their definitions in Table 1) are shown in Figure 7 where similar minor constituents in semidiurnal (S_2 , N_2) and diurnal (O_1 , K_1) band behave more or less the same. As shown in Figure 7a, the minor constituents S_2 , N_2 , O_1 , and K_1 experience more friction compared with the predominant M_2 tide. Interestingly, we observe a stronger damping ($\delta_A < 0$) of semidiurnal constituents (S_2 , N_2) than those of diurnal constituents (O_1 , K_1) in the seaward part of the estuary (around $x=0$ -40
305 km) although the amplitudes of the diurnal constituents are less than those of the semidiurnal ones. In contrast, the amplification ($\delta_A > 0$) of semidiurnal constituents (S_2 , N_2) is more apparent than those of diurnal constituents (O_1 , K_1) in the landward part of the estuary. For the wave celerity, as
310 expected the dominant M_2 tide travels faster (smaller λ_A) than minor tidal constituents. In addition, we observe that the wave celerity of semidiurnal tidal constituents is larger than those of diurnal constituents in the seaward reach (around $x=0$ -30 km), while it is the opposite in the landward reach, which suggests a complex relation between tidal damping/amplification and wave celerity due to the combined impacts of channel convergence, bottom friction and reflected wave.

For the Guadalquivir estuary, the geometry can be approximated as a converging estuary with a width convergence length of $b=65.5$ km and a constant stream depth of about 7.1 m. A linear
315 reduction of the storage width ratio of 1.5-1 was adopted over the reach 0-103 km. The observed tidal amplitudes and phases are best reproduced by using the model for $K = 46 \text{ m}^{1/3}\text{s}^{-1}$ (see Figure 8). In general, the observed tidal properties (tidal amplitude and phase) of different constituents are well reproduced. The enhanced frictional coefficient f for minor constituents S_2 , N_2 , O_1 , and K_1 are 5.4, 9.7, 40.7, and 43.7, respectively (Table 3).

320 Figure 9 shows the longitudinal variations of tidal damping/amplification and wave celerity for the Guadalquivir estuary. Similar to the Guadiana estuary, we observe that the dominant M_2 tide experiences less tidal damping and travels faster than other minor tidal constituents. It can be seen from Figure 9 that the magnitude of tidal damping is approximately one order larger than that in



the Guadiana estuary (Figure 9a) and hence the wave celerity is comparatively smaller (larger λ_A ,
325 Figure 9b). Unlike the Guadiana estuary, the damping experienced by the minor semidiurnal tides
is less than those of diurnal constituents in the seaward reach (around $x=0-55$ km), while the wave
celerity is consistently larger for the whole channel.

5 Conclusions

In this study, we provide insight into the mutual interactions between one predominant (e.g., M_2)
330 and other tidal constituents in estuaries and the role of quadratic friction on tidal wave propagation.
An analytical method exploiting the Chebyshev polynomials was developed to quantify the effective
friction experienced by different tidal constituents. Based on the linearization of the quadratic
friction, the conceptual model has been used to explore the nonlinear interaction of different tidal
constituents, which enables them to be treated independently by means of an iterative procedure.
335 Thus, an analytical hydrodynamic model for a single tidal constituent can be used to reproduce the
correct wave behavior for different tidal constituents. In particular, it was shown that a correction
of the friction term needs to be used to correctly reproduce the tidal dynamics for minor tidal constituents.
The application to the Guadiana and the Guadalquivir estuaries shows that the conceptual
model can interpret the nonlinear interaction reasonably well when combined with an analytical
340 model for tidal hydrodynamics.

A crucial feature of the proposed approach is the deterministic description of the mutual frictional
interaction among tidal constituents, which avoids the need of an independent calibration of the
friction parameter for the single constituent. In this respect, further work is required to explore
whether a reliable value of the friction coefficient estimated through this method can be parametrized
345 based on observations of the bottom roughness of the estuary.

Appendix A

Analytical solutions of tidal hydrodynamics for a single tidal constituent

In this paper, analytical solutions for a semi-closed estuary proposed by Toffolon and Savenije (2011)
350 were used to reproduce the longitudinal tidal dynamics along the estuary axis. The solution makes
use of the parameters that are defined in Table 1.

The analytical solutions for the tidal wave amplitudes and phases are given by:

$$\eta = \zeta_0 \bar{h}_0 |A^*|, \quad v = r_S \zeta_0 c_0 |V^*|, \quad (A1)$$

$$\tan(\phi_A) = \frac{\Im(A^*)}{\Re(A^*)}, \quad \tan(\phi_V) = \frac{\Im(V^*)}{\Re(V^*)}, \quad (A2)$$



355 where \Re and \Im are the real and image parts of the corresponding term, and A^* and V^* are unknown complex functions varying along the dimensionless coordinate $x^* = x/L_0$:

$$A^* = a_1^* \exp(w_1^* x^*) + a_2^* \exp(w_2^* x^*), \quad (\text{A3})$$

$$V^* = v_1^* \exp(w_1^* x^*) + v_2^* \exp(w_2^* x^*). \quad (\text{A4})$$

360 For a tidal channel with a closed end, the analytical solutions for the unknown variables in Eqs. (A3) and (A4) are listed in Table 4, where Λ is a complex variable, defined as

$$\Lambda = \sqrt{\gamma^2/4 - 1 + i\hat{\chi}}, \quad \hat{\chi} = \frac{8}{3\pi} \mu \chi, \quad (\text{A5})$$

where the coefficient $8/(3\pi)$ stems from the adoption of Lorentz's linearization when considering only one single predominant tidal constituent (e.g., M_2).

365 Since the friction parameter $\hat{\chi}$ depends on the unknown value of μ (or v), an iterative procedure was used to determine the correct wave behavior. In addition, to account for the longitudinal variation of the cross-section (e.g., estuary depth) a multi-reach technique was adopted by subdividing the entire estuary into multiple sub-reaches and the solutions obtained by solving a set of linear equations with internal boundary conditions at the junction of the sub-reaches satisfying the continuity 370 condition (see details in Toffolon and Savenije, 2011).

For given computed values of A^* and V^* , the dependent parameters defined in Table 1 can be computed using the following equations:

$$\mu = |V^*|, \quad \phi = \phi_V - \phi_A, \quad (\text{A6})$$

$$375 \quad \delta_A = \Re\left(\frac{1}{A^*} \frac{dA^*}{dx^*}\right), \quad \delta_V = \Re\left(\frac{1}{V^*} \frac{dV^*}{dx^*}\right), \quad (\text{A7})$$

$$\lambda_A = \left| \Im\left(\frac{1}{A^*} \frac{dA^*}{dx^*}\right) \right|, \quad \lambda_V = \left| \Im\left(\frac{1}{V^*} \frac{dV^*}{dx^*}\right) \right|. \quad (\text{A8})$$

Appendix B

Coefficients of the Godin's expansion

380 The following trigonometric equation

$$\cos^3(\omega_1 t) = \frac{3}{4} \cos(\omega_1 t) + \frac{1}{4} \cos(3\omega_1 t), \quad (\text{B1})$$

is used to convert the third-order terms of Eq. (7) to the harmonic constituents. For a single harmonic, it follows that



$$u|u| = v_1^2 \left[\left(\alpha + \frac{3}{4} \beta \right) \cos(\omega_1 t) + \frac{1}{4} \beta \cos(3\omega_1 t) \right]. \quad (\text{B2})$$

385 For two harmonic constituents, the Chebyshev polynomials approximation of $u|u|$ is expressed as

$$u|u| = v_1^2 \left\{ \alpha [\varepsilon_1 \cos(\omega_1 t) + \varepsilon_2 \cos(\omega_2 t)] + \beta [\varepsilon_1 \cos(\omega_1 t) + \varepsilon_2 \cos(\omega_2 t)]^3 \right\}. \quad (\text{B3})$$

In Eq. (B3), the cubic term can be expanded as

$$\begin{aligned} [\varepsilon_1 \cos(\omega_1 t) + \varepsilon_2 \cos(\omega_2 t)]^3 = & \varepsilon_1^3 \cos^3(\omega_1 t) + 3\varepsilon_1 \varepsilon_2^2 \cos(\omega_1 t) \cos^2(\omega_2 t) \\ & + 3\varepsilon_2 \varepsilon_1^2 \cos(\omega_2 t) \cos^2(\omega_1 t) + \varepsilon_2^3 \cos^3(\omega_2 t). \end{aligned} \quad (\text{B4})$$

Making use of the trigonometric equations to expand the power of the cosine functions (e.g.,
 390 $\cos^3(\omega_1 t)$ and $\cos^2(\omega_1 t)$) and extracting only the harmonic terms with frequencies ω_1 and ω_2 , Eq.
 (B3) can be reduced to Eq. (12).

For the case of many constituents, here we only provide the exact coefficients for $n=3$:

$$F_1 = \frac{3\pi}{8} \left[\alpha + \beta \left(\frac{3}{4} \varepsilon_1^2 + \frac{3}{2} \varepsilon_2^2 + \frac{3}{2} \varepsilon_3^2 \right) \right] = \frac{1}{5} (2 + 3\varepsilon_1^2 + 6\varepsilon_2^2 + 6\varepsilon_3^2), \quad (\text{B5})$$

$$395 \quad F_2 = \frac{3\pi}{8} \left[\alpha + \beta \left(\frac{3}{4} \varepsilon_2^2 + \frac{3}{2} \varepsilon_1^2 + \frac{3}{2} \varepsilon_3^2 \right) \right] = \frac{1}{5} (2 + 3\varepsilon_2^2 + 6\varepsilon_1^2 + 6\varepsilon_3^2), \quad (\text{B6})$$

$$F_3 = \frac{3\pi}{8} \left[\alpha + \beta \left(\frac{3}{4} \varepsilon_3^2 + \frac{3}{2} \varepsilon_1^2 + \frac{3}{2} \varepsilon_2^2 \right) \right] = \frac{1}{5} (2 + 3\varepsilon_3^2 + 6\varepsilon_1^2 + 6\varepsilon_2^2). \quad (\text{B7})$$

Equations (B5) to (B6) reduce to Eqs. (13) and (14) when $\varepsilon_3 = 0$ (i.e., $v_3=0$).

Acknowledgements. We acknowledge the financial support from the National Key R&D of China (Grant No.
 400 2016YFC0402600), from the National Natural Science Foundation of China (Grant No. 51709287), from the
 Basic Research Program of Sun Yat-Sen University (Grant No. 17lgzd12) and from the Water Resource Science
 and Technology Innovation Program of Guangdong Province (Grant No. 2016-20). The work of the fifth author
 was supported by FCT research contract IF/00661/2014/CP1234.



References

405 Cai, H., Toffolon, M., and Savenije, H. H. G.: Analytical investigation of superposition between predominant M_2 and other tidal constituents in estuaries, in: Proceedings of 36th IAHR World Congress, Delft–The Hague, 2015.

Cai, H., Toffolon, M., and Savenije, H. H. G.: An Analytical Approach to Determining Resonance in Semi-Closed Convergent Tidal Channels, *Coast Eng. J.*, 58, doi:Artn 1650009 10.1142/S0578563416500091, 410 2016.

Diez-Minguito, M., Baquerizo, A., Ortega-Sánchez, M., Navarro, G., and Losada, M. A.: Tide transformation in the Guadalquivir estuary (SW Spain) and process-based zonation, *J. Geophys. Res.*, 117, doi:10.1029/2011jc007344, 2012.

Doodson, A. T.: Perturbations of Harmonic Tidal Constants, in: *Proceedings of the Royal Society*, vol. 106 of 415 739, pp. 513–526, London, 1924.

Dronkers, J. J.: *Tidal computations in River and Coastal Waters*, Elsevier, New York, 1964.

Fang, G.: Nonlinear effects of tidal friction, *Acta Oceanol. Sin.*, 6 (Suppl.), 105–122, 1987.

Garel, E.: Guadiana River estuary - Investigating the past, present and future, in: *Present Dynamics of the 420 Guadiana Estuary*, edited by Moura, D., Gomes, A., Mendes, I., and Aníbal, J., pp. 15–37, University of Algarve, Faro, Portugal, 2017.

Garel, E. and Ferreira, O.: Fortnightly changes in water transport direction across the mouth of a narrow estuary, *Estuar. Coast*, 36, 286–299, doi:10.1007/s12237-012-9566-z, 2013.

Garel, E., Pinto, L., Santos, A., and Ferreira, O.: Tidal and river discharge forcing upon water and sediment circulation at a rock-bound estuary (Guadiana estuary, Portugal), *Estuar. Coast. Shelf S.*, 84, 269–281, 425 doi:10.1016/j.ecss.2009.07.002, 2009.

Godin, G.: Compact Approximations to the Bottom Friction Term, for the Study of Tides Propagating in Channels, *Cont. Shelf Res.*, 11, 579–589, doi:10.1016/0278-4343(91)90013-V, 1991.

Godin, G.: The propagation of tides up rivers with special considerations on the upper Saint Lawrence river, *Estuar. Coast. Shelf S.*, 48, 307–324, doi:10.1006/ecss.1998.0422, 1999.

430 Heaps, N. S.: Linearized vertically-integrated equation for residual circulation in coastal seas, *Dtsch. Hydrogr. Z.*, 31, 147–169, doi:10.1007/BF02224467, 1978.

Inoue, R. and Garrett, C.: Fourier representation of quadratic friction, *J. Phys. Oceanogr.*, 37, 593–610, doi:10.1175/Jpo2999.1, 2007.

Jeffreys, H.: *The Earth: Its Origin, History and Physical Constitution* (5th ed.), Cambridge University Press, 435 U.K., 1970.

Kabbaj, A. and Le Provost, C.: Nonlinear tidal waves in channels: a perturbation method adapted to the importance of quadratic bottom friction, *Tellus*, 32, 143–163, doi:10.1111/j.2153-3490.1980.tb00942.x, 1980.

Le Provost, C.: Décomposition spectrale du terme quadratique de frottement dans les équations des marées littorales, *C.R. Acad. Sci. Paris*, 276, 653–656, 1973.

440 Le Provost, C.: Generation of Overtides and compound tides (review), in: *Tidal Hydrodynamics*, edited by Parker, B., pp. 269–295, John Wiley and Sons, Hoboken, N. J., 1991.

Le Provost, C. and Fornerino, M.: Tidal spectroscopy of the English Channel with a numerical model, *J. Phys. Oceanogr.*, 15, 1009–1031, doi:10.1175/1520-0485(1985)015<1009:TSOTEC>2.0.CO;2, 1985.



Le Provost, C., Rougier, G., and Poncet, A.: Numerical modeling of the harmonic constituents of the tides, with application to the English Channel, *J. Phys. Oceanogr.*, 11, 1123–1138, doi:10.1175/1520-0485(1981)011<1123:NMOTHC>2.0.CO;2, 1981.

Lorentz, H. A.: *Verslag Staatscommissie Zuiderzee* (in Dutch), Tech. rep., Alg. Landsdrukkerij, 1926.

Molines, J. M., Fornerino, M., and Le Provost, C.: Tidal spectroscopy of a coastal area: observed and simulated tides of the Lake Maracaibo system, *Cont. Shelf Res.*, 9, 301–323, doi:10.1016/0278-4343(89)90036-8, 1989.

Parker, B. B.: The relative importance of the various nonlinear mechanisms in a wide range of tidal interactions, in: *Tidal Hydrodynamics*, edited by Parker, B., pp. 237–268, John Wiley and Sons, Hoboken, N. J., 1991.

Pawlowicz, R., Beardsley, B., and Lentz, S.: Classical tidal harmonic analysis including error estimates in MATLAB using T-TIDE, *Comput. Geosci.*, 28, 929–937, doi:10.1016/S0098-3004(02)00013-4, 2002.

Pingree, R. D.: Spring Tides and Quadratic Friction, *Deep-Sea Res. Part A-Oceanographic Research Papers*, 30, 929–944, doi:10.1016/0198-0149(83)90049-3, 1983.

Prandle, D.: The influence of bed friction and vertical eddy viscosity on tidal propagation, *Cont. Shelf Res.*, 17, 1367–1374, doi:10.1016/S0278-4343(97)00013-7, 1997.

Proudman, J.: *Dynamical oceanography*, Methuen, London, 1953.

Savenije, H. H. G., Toffolon, M., Haas, J., and Veling, E. J. M.: Analytical description of tidal dynamics in convergent estuaries, *J. Geophys. Res.*, 113, doi:10.1029/2007JC004408, 2008.

Schutteelaars, H. M., de Jonge, V. N., and Chernetsky, A.: Improving the predictive power when modelling physical effects of human interventions in estuarine systems, *Ocean Coast. Manage.*, 79, 70–82, doi:10.1016/j.ocecoaman.2012.05.009, 2013.

Toffolon, M. and Savenije, H. H. G.: Revisiting linearized one-dimensional tidal propagation, *J. Geophys. Res.*, 116, doi:10.1029/2010JC006616, 2011.

Winterwerp, J. C., Wang, Z. B., van Braeckel, A., van Holland, G., and Kosters, F.: Man-induced regime shifts in small estuaries-II: a comparison of rivers, *Ocean Dynam.*, 63, 1293–1306, doi:10.1007/s10236-013-0663-8, 2013.



Table 1. Definitions of dimensionless parameters.

Independent parameters	Dependent parameters
Tidal amplitude at the mouth	Tidal amplitude
$\zeta_0 = \eta_0/\bar{h}_0$	$\zeta = \eta/\bar{h}$
Friction number at the mouth	Friction number
$\chi_0 = r_S c_0 \zeta_0 g / (K^2 \omega \bar{h}_0^{4/3})$	$\chi = r_S c_0 \zeta g / (K^2 \omega \bar{h}^{4/3})$
Estuary shape	Velocity number
$\gamma = c_0 / (\omega a)$	$\mu = v / (r_S \zeta c_0) = v \bar{h} / (r_S \eta c_0)$
Estuary length	Damping number for water level
$L_e^* = L_e / L_0$	$\delta_A = c_0 d\eta / (\eta \omega dx)$
	Damping number for velocity
	$\delta_V = c_0 dv / (v \omega dx)$
	Celerity number for water level
	$\lambda_A = c_0 / c_A$
	Celerity number for velocity
	$\lambda_V = c_0 / c_V$
	Phase difference
	$\phi = \phi_V - \phi_A$



Table 2. Tidal elevation amplitudes (m) and phases (°) estimates (with 95% confidence intervals in brackets) from harmonic analyses of pressure records along the Guadiana estuary (x : distance from the mouth, km).

x (km)	Amplitude (m)							
	M_{sf}	O_1	K_1	N_2	M_2	S_2	M_4	M_6
2.4	0.01 (0.03)	0.06 (0.01)	0.07 (0.01)	0.23 (0.01)	0.97 (0.01)	0.37 (0.02)	0.02 (0.00)	0.01 (0.00)
10.7	0.01 (0.07)	0.06 (0.01)	0.07 (0.01)	0.22 (0.01)	0.93 (0.01)	0.34 (0.01)	0.02 (0.01)	0.01 (0.00)
22.8	0.03 (0.04)	0.06 (0.01)	0.07 (0.01)	0.20 (0.02)	0.86 (0.02)	0.29 (0.02)	0.04 (0.01)	0.02 (0.01)
33.9	0.06 (0.05)	0.06 (0.01)	0.07 (0.01)	0.20 (0.02)	0.85 (0.02)	0.27 (0.02)	0.04 (0.01)	0.03 (0.01)
43.6	0.06 (0.06)	0.06 (0.01)	0.07 (0.01)	0.21 (0.02)	0.87 (0.02)	0.27 (0.02)	0.05 (0.01)	0.03 (0.01)
51.4	0.05 (0.05)	0.06 (0.01)	0.07 (0.01)	0.22 (0.02)	0.90 (0.02)	0.28 (0.02)	0.07 (0.01)	0.03 (0.01)
60.1	0.07 (0.06)	0.06 (0.01)	0.07 (0.01)	0.22 (0.02)	0.93 (0.02)	0.30 (0.02)	0.08 (0.01)	0.04 (0.01)
69.6	0.10 (0.06)	0.06 (0.01)	0.06 (0.01)	0.19 (0.03)	0.78 (0.03)	0.24 (0.03)	0.16 (0.03)	0.02 (0.01)
Phase (°)								
2.4	190 (149)	310 (6)	73 (5)	54 (4)	62 (1)	93 (2)	151 (8)	219 (18)
10.7	8 (190)	319 (7)	85 (6)	68 (3)	75 (1)	108 (3)	103 (14)	237 (15)
22.8	38 (66)	331 (9)	103 (7)	87 (4)	93 (1)	130 (3)	131 (12)	294 (16)
33.9	49 (56)	343 (7)	116 (6)	104 (5)	109 (1)	151 (4)	166 (8)	336 (11)
43.6	51 (58)	348 (8)	123 (8)	116 (5)	121 (1)	166 (4)	189 (6)	12 (14)
51.4	48 (48)	352 (9)	128 (8)	123 (6)	128 (1)	175 (5)	203 (5)	43 (19)
60.1	53 (58)	356 (9)	133 (8)	131 (6)	135 (1)	184 (5)	219 (4)	69 (21)
69.6	51 (43)	7 (9)	146 (8)	146 (9)	148 (2)	200 (7)	261 (11)	15 (18)

Table 3. Mean correction friction factor f for different tidal constituents along the Guadiana and the Guadalquivir estuaries.

Tidal constituents	M_2	S_2	N_2	K_1	O_1
Guadiana	1.1	4.6	8.1	41.1	49.8
Guadalquivir	1.1	5.4	9.7	40.7	43.7

Table 4. Analytical expressions for unknown complex variables for the case of a closed estuary.

a_1^*, a_2^*	v_1^*, v_2^*	w_1^*, w_2^*
$a_1^* = \left[1 + \exp(\Lambda L_e^*) \frac{\Lambda + \gamma/2}{\Lambda - \gamma/2}\right]^{-1}$	$v_1^* = \frac{-ia_1^*}{\Lambda - \gamma/2}$	$w_1^* = \gamma/2 + \Lambda$
$a_2^* = 1 - a_1^*$	$v_2^* = \frac{i(1 - a_1^*)}{\Lambda + \gamma/2}$	$w_2^* = \gamma/2 - \Lambda$




Figure 1. Geometry of a semi-closed estuary and basic notation (after Savenije et al. (2008)). HW, high water; LW, low water.




Figure 2. Tidally averaged depth (m, black dots), width (m, blue dots) and cross-sectional area (m^2 , green dots) along the Guadiana estuary. Red lines represent exponential fit curves for the width and cross-sectional area.




Figure 3. Approximation to the quadratic velocity $u|u|$ by the Chebyshev polynomials approach for the case of two tidal constituents (i.e., M_2 and K_1). Here, $u = 0.6 \cos(\omega_1 t) + 0.2 \cos(\omega_2 t)$, where ω_1 and ω_2 represent the tidal frequencies of M_2 and K_1 , respectively.




Figure 4. Computed effective friction coefficients F_1 (a) and F_2 (b) from Eqs. (13) and (14) as a function of ε_1 .




Figure 5. Computation process for tidal properties of different constituents in an estuary.




Figure 6. Tidal constituents (a) M_2 ; (b) S_2 ; (c) N_2 ; (d) K_1 ; (e) O_1 : modelled against observed values of tidal amplitude (m) and phase (°) of elevation along the Guadiana estuary.




Figure 7. Longitudinal variations of tidal damping/amplification number δ_A (a) and wave celerity number λ_A (b) for different tidal constituents along the Guadiana estuary.




Figure 8. Tidal constituents (a) M_2 ; (b) S_2 ; (c) N_2 ; (d) K_1 ; (e) O_1 : modelled against observed values of tidal amplitude (m) and phase ($^{\circ}$) of elevation along the Guadalquivir estuary.




Figure 9. Longitudinal variations of tidal damping/amplification number δ_A (a) and wave celerity number λ_A (b) for different tidal constituents along the Guadalquivir estuary.